

# Series 82

## Characteristics

The compact Series 82 is especially suited for:

- Flush design

The robust construction and the metal housing allow a high vandal resistant, which approximate a mechanical front protection of IK10.

## Functions

The Series 82 incorporates the following functions:

- Indicator
- Pushbutton
- Illuminated pushbutton

## Market segments

The EAO series 82 is used in the following segments:

- Machinery and Automation
- Building technology
- Panel building

Please refer to the EAO website to obtain detailed information regarding this series [www.products.eao.com](http://www.products.eao.com)  
Configure a product to your exact needs and request a quotation.





**Overview****Flush design**

Indicator Ø 16 mm	4
Indicator Ø 19 mm	14
Indicator Ø 22 mm	24
Pushbutton Ø 16 mm	34
Pushbutton Ø 19 mm	38
Pushbutton Ø 22 mm	42
Illuminated pushbutton Ø 16 mm	46
Illuminated pushbutton Ø 19 mm	65
Illuminated pushbutton Ø 22 mm	84

<b>Drawings</b>	<b>103</b>
-----------------	------------

<b>Technical data</b>	<b>104</b>
-----------------------	------------

<b>Application guidelines</b>	<b>106</b>
-------------------------------	------------


<b>Index</b>	<b>107</b>
--------------	------------

# 82 Flush design

Indicator 16 mm, IP 65 & IP 67




Product can differ from the current configuration.




Dimensions [mm]  
L1 = Solder/Plug-in terminal 2.8 x 0.5 mm,  
X = Screw terminal

Equipment consisting of (schematic overview)



Each Part Number listed below includes all the black components shown in the 3D-drawing.



Mounting cut-outs [mm]

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
 <p><b>Indicator 16 mm stainless-steel, Front dimension Ø 18 mm</b></p>									
Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.0112</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.0113</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.0114</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.0115</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.0116</b>	1	1	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.0122</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.0123</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.0124</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.0125</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.0126</b>	1	1	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.0132</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.0133</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.0134</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.0135</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.0136</b>	1	1	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.0142</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.0143</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.0144</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.0145</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.0146</b>	1	1	0.018 kg

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.0152</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.0153</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.0154</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.0155</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.0156</b>	1	1	0.018 kg


**Indicator 16 mm stainless-steel, Front dimension Ø 18 mm**

Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.0212</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.0213</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.0214</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.0215</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.0216</b>	1	1	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.0222</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.0223</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.0224</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.0225</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.0226</b>	1	1	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.0232</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.0233</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.0234</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.0235</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.0236</b>	1	1	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.0242</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.0243</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.0244</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.0245</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.0246</b>	1	1	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.0252</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.0253</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.0254</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.0255</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.0256</b>	1	1	0.021 kg


**Indicator 16 mm stainless-steel chrome-coloured, Front dimension Ø 18 mm**

Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.0112</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.0113</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.0114</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.0115</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.0116</b>	1	1	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.0122</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.0123</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.0124</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.0125</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.0126</b>	1	1	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.0132</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.0133</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.0134</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.0135</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.0136</b>	1	1	0.018 kg

# 82 Flush design

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.0142</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.0143</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.0144</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.0145</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.0146</b>	1	1	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.0152</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.0153</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.0154</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.0155</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.0156</b>	1	1	0.018 kg
 <p><b>Indicator 16 mm stainless-steel chrome-coloured, Front dimension Ø 18 mm</b></p>									
Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.0212</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.0213</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.0214</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.0215</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.0216</b>	1	1	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.0222</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.0223</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.0224</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.0225</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.0226</b>	1	1	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.0232</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.0233</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.0234</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.0235</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.0236</b>	1	1	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.0242</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.0243</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.0244</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.0245</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.0246</b>	1	1	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.0252</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.0253</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.0254</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.0255</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.0256</b>	1	1	0.021 kg

illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
 <p><b>Indicator 16 mm Brass, Front dimension Ø 18 mm</b></p>									
Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.0112</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.0113</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.0114</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.0115</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.0116</b>	1	1	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.0122</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.0123</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.0124</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.0125</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.0126</b>	1	1	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.0132</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.0133</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.0134</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.0135</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.0136</b>	1	1	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.0142</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.0143</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.0144</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.0145</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.0146</b>	1	1	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.0152</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.0153</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.0154</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.0155</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.0156</b>	1	1	0.018 kg

 <p><b>Indicator 16 mm Brass, Front dimension Ø 18 mm</b></p>									
Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.0212</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.0213</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.0214</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.0215</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.0216</b>	1	1	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.0222</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.0223</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.0224</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.0225</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.0226</b>	1	1	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.0232</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.0233</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.0234</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.0235</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.0236</b>	1	1	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.0242</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.0243</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.0244</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.0245</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.0246</b>	1	1	0.021 kg

# 82 Flush design

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.0252</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.0253</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.0254</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.0255</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.0256</b>	1	1	0.021 kg



### Indicator 16 mm Aluminium, Front dimension Ø 18 mm

Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.0112</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.0113</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.0114</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.0115</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.0116</b>	1	1	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.0122</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.0123</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.0124</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.0125</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.0126</b>	1	1	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.0132</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.0133</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.0134</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.0135</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.0136</b>	1	1	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.0142</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.0143</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.0144</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.0145</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.0146</b>	1	1	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.0152</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.0153</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.0154</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.0155</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.0156</b>	1	1	0.018 kg



### Indicator 16 mm Aluminium, Front dimension Ø 18 mm

Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.0212</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.0213</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.0214</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.0215</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.0216</b>	1	1	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.0222</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.0223</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.0224</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.0225</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.0226</b>	1	1	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.0232</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.0233</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.0234</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.0235</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.0236</b>	1	1	0.021 kg

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.0242</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.0243</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.0244</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.0245</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.0246</b>	1	1	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.0252</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.0253</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.0254</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.0255</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.0256</b>	1	1	0.021 kg



**Indicator 16 mm stainless-steel, Front dimension Ø 18 mm**

Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4152.0112</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4152.0113</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4152.0114</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4152.0115</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4152.0116</b>	1	1	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4152.0122</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4152.0123</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4152.0124</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4152.0125</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4152.0126</b>	1	1	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4152.0132</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4152.0133</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4152.0134</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4152.0135</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4152.0136</b>	1	1	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4152.0142</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4152.0143</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4152.0144</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4152.0145</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4152.0146</b>	1	1	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4152.0152</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4152.0153</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4152.0154</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4152.0155</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4152.0156</b>	1	1	0.018 kg



**Indicator 16 mm stainless-steel, Front dimension Ø 18 mm**

Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4152.0212</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4152.0213</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4152.0214</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4152.0215</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4152.0216</b>	1	1	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4152.0222</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4152.0223</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4152.0224</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4152.0225</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4152.0226</b>	1	1	0.021 kg

# 82 Flush design

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4152.0232</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4152.0233</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4152.0234</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4152.0235</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4152.0236</b>	1	1	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4152.0242</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4152.0243</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4152.0244</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4152.0245</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4152.0246</b>	1	1	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4152.0252</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4152.0253</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4152.0254</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4152.0255</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4152.0256</b>	1	1	0.021 kg
 <p><b>Indicator 16 mm stainless-steel chrome-coloured, Front dimension Ø 18 mm</b></p>									
Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4252.0112</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4252.0113</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4252.0114</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4252.0115</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4252.0116</b>	1	1	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4252.0122</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4252.0123</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4252.0124</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4252.0125</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4252.0126</b>	1	1	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4252.0132</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4252.0133</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4252.0134</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4252.0135</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4252.0136</b>	1	1	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4252.0142</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4252.0143</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4252.0144</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4252.0145</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4252.0146</b>	1	1	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4252.0152</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4252.0153</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4252.0154</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4252.0155</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4252.0156</b>	1	1	0.018 kg

illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
 <p><b>Indicator 16 mm stainless-steel chrome-coloured, Front dimension Ø 18 mm</b></p>									
Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4252.0212</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4252.0213</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4252.0214</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4252.0215</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4252.0216</b>	1	1	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4252.0222</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4252.0223</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4252.0224</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4252.0225</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4252.0226</b>	1	1	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4252.0232</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4252.0233</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4252.0234</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4252.0235</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4252.0236</b>	1	1	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4252.0242</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4252.0243</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4252.0244</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4252.0245</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4252.0246</b>	1	1	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4252.0252</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4252.0253</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4252.0254</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4252.0255</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4252.0256</b>	1	1	0.021 kg
 <p><b>Indicator 16 mm Brass, Front dimension Ø 18 mm</b></p>									
Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4352.0112</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4352.0113</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4352.0114</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4352.0115</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4352.0116</b>	1	1	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4352.0122</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4352.0123</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4352.0124</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4352.0125</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4352.0126</b>	1	1	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4352.0132</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4352.0133</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4352.0134</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4352.0135</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4352.0136</b>	1	1	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4352.0142</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4352.0143</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4352.0144</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4352.0145</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4352.0146</b>	1	1	0.018 kg

# 82 Flush design

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4352.0152</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4352.0153</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4352.0154</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4352.0155</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4352.0156</b>	1	1	0.018 kg



### Indicator 16 mm Brass, Front dimension Ø 18 mm

Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4352.0212</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4352.0213</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4352.0214</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4352.0215</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4352.0216</b>	1	1	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4352.0222</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4352.0223</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4352.0224</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4352.0225</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4352.0226</b>	1	1	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4352.0232</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4352.0233</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4352.0234</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4352.0235</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4352.0236</b>	1	1	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4352.0242</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4352.0243</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4352.0244</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4352.0245</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4352.0246</b>	1	1	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4352.0252</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4352.0253</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4352.0254</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4352.0255</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4352.0256</b>	1	1	0.021 kg



### Indicator 16 mm Aluminium, Front dimension Ø 18 mm

Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4552.0112</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4552.0113</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4552.0114</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4552.0115</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4552.0116</b>	1	1	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4552.0122</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4552.0123</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4552.0124</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4552.0125</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4552.0126</b>	1	1	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4552.0132</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4552.0133</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4552.0134</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4552.0135</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4552.0136</b>	1	1	0.018 kg


Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4552.0142</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4552.0143</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4552.0144</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4552.0145</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4552.0146</b>	1	1	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4552.0152</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4552.0153</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4552.0154</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4552.0155</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4552.0156</b>	1	1	0.018 kg



### Indicator 16 mm Aluminium, Front dimension Ø 18 mm

Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4552.0212</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4552.0213</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4552.0214</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4552.0215</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4552.0216</b>	1	1	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4552.0222</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4552.0223</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4552.0224</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4552.0225</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4552.0226</b>	1	1	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4552.0232</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4552.0233</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4552.0234</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4552.0235</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4552.0236</b>	1	1	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4552.0242</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4552.0243</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4552.0244</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4552.0245</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4552.0246</b>	1	1	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4552.0252</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4552.0253</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4552.0254</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4552.0255</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4552.0256</b>	1	1	0.021 kg

The component layouts you will find from page 103




# 82 Flush design

Indicator 19 mm, IP 65 & IP 67




Product can differ from the current configuration.




Dimensions [mm]  
L1 = Solder/Plug-in terminal 2.8 x 0.5 mm,  
X = Screw terminal

Equipment consisting of (schematic overview)



Each Part Number listed below includes all the black components shown in the 3D-drawing.



Mounting cut-outs [mm]

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
 <p><b>Indicator 19 mm stainless-steel, Front dimension Ø 22 mm</b></p>									
Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.0112</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.0113</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.0114</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.0115</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.0116</b>	1	1	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.0122</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.0123</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.0124</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.0125</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.0126</b>	1	1	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.0132</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.0133</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.0134</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.0135</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.0136</b>	1	1	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.0142</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.0143</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.0144</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.0145</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.0146</b>	1	1	0.018 kg

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.0152</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.0153</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.0154</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.0155</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.0156</b>	1	1	0.018 kg


**Indicator 19 mm stainless-steel, Front dimension Ø 22 mm**

Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.0212</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.0213</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.0214</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.0215</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.0216</b>	1	1	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.0222</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.0223</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.0224</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.0225</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.0226</b>	1	1	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.0232</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.0233</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.0234</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.0235</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.0236</b>	1	1	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.0242</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.0243</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.0244</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.0245</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.0246</b>	1	1	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.0252</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.0253</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.0254</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.0255</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.0256</b>	1	1	0.021 kg


**Indicator 19 mm stainless-steel chrome-coloured, Front dimension Ø 22 mm**

Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.0112</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.0113</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.0114</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.0115</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.0116</b>	1	1	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.0122</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.0123</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.0124</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.0125</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.0126</b>	1	1	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.0132</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.0133</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.0134</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.0135</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.0136</b>	1	1	0.018 kg

# 82 Flush design

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.0142</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.0143</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.0144</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.0145</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.0146</b>	1	1	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.0152</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.0153</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.0154</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.0155</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.0156</b>	1	1	0.018 kg
 <p><b>Indicator 19 mm stainless-steel chrome-coloured, Front dimension Ø 22 mm</b></p>									
Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.0212</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.0213</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.0214</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.0215</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.0216</b>	1	1	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.0222</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.0223</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.0224</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.0225</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.0226</b>	1	1	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.0232</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.0233</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.0234</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.0235</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.0236</b>	1	1	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.0242</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.0243</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.0244</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.0245</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.0246</b>	1	1	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.0252</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.0253</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.0254</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.0255</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.0256</b>	1	1	0.021 kg

illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
 <p><b>Indicator 19 mm Brass, Front dimension Ø 22 mm</b></p>									
Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.0112</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.0113</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.0114</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.0115</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.0116</b>	1	1	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.0122</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.0123</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.0124</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.0125</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.0126</b>	1	1	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.0132</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.0133</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.0134</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.0135</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.0136</b>	1	1	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.0142</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.0143</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.0144</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.0145</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.0146</b>	1	1	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.0152</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.0153</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.0154</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.0155</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.0156</b>	1	1	0.018 kg

 <p><b>Indicator 19 mm Brass, Front dimension Ø 22 mm</b></p>									
Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.0212</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.0213</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.0214</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.0215</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.0216</b>	1	1	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.0222</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.0223</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.0224</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.0225</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.0226</b>	1	1	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.0232</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.0233</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.0234</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.0235</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.0236</b>	1	1	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.0242</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.0243</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.0244</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.0245</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.0246</b>	1	1	0.021 kg

# 82 Flush design

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.0252</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.0253</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.0254</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.0255</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.0256</b>	1	1	0.021 kg



### Indicator 19 mm Aluminium, Front dimension Ø 22 mm

Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.0112</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.0113</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.0114</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.0115</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.0116</b>	1	1	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.0122</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.0123</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.0124</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.0125</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.0126</b>	1	1	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.0132</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.0133</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.0134</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.0135</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.0136</b>	1	1	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.0142</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.0143</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.0144</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.0145</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.0146</b>	1	1	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.0152</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.0153</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.0154</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.0155</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.0156</b>	1	1	0.018 kg



### Indicator 19 mm Aluminium, Front dimension Ø 22 mm

Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.0212</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.0213</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.0214</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.0215</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.0216</b>	1	1	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.0222</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.0223</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.0224</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.0225</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.0226</b>	1	1	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.0232</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.0233</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.0234</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.0235</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.0236</b>	1	1	0.021 kg

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.0242</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.0243</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.0244</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.0245</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.0246</b>	1	1	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.0252</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.0253</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.0254</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.0255</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.0256</b>	1	1	0.021 kg



**Indicator 19 mm stainless-steel, Front dimension Ø 22 mm**

Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5152.0112</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5152.0113</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5152.0114</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5152.0115</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5152.0116</b>	1	1	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5152.0122</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5152.0123</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5152.0124</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5152.0125</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5152.0126</b>	1	1	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5152.0132</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5152.0133</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5152.0134</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5152.0135</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5152.0136</b>	1	1	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5152.0142</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5152.0143</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5152.0144</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5152.0145</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5152.0146</b>	1	1	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5152.0152</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5152.0153</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5152.0154</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5152.0155</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5152.0156</b>	1	1	0.018 kg



**Indicator 19 mm stainless-steel, Front dimension Ø 22 mm**

Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5152.0212</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5152.0213</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5152.0214</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5152.0215</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5152.0216</b>	1	1	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5152.0222</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5152.0223</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5152.0224</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5152.0225</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5152.0226</b>	1	1	0.021 kg

# 82 Flush design

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5152.0232</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5152.0233</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5152.0234</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5152.0235</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5152.0236</b>	1	1	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5152.0242</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5152.0243</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5152.0244</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5152.0245</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5152.0246</b>	1	1	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5152.0252</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5152.0253</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5152.0254</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5152.0255</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5152.0256</b>	1	1	0.021 kg
 <p><b>Indicator 19 mm stainless-steel chrome-coloured, Front dimension Ø 22 mm</b></p>									
Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5252.0112</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5252.0113</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5252.0114</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5252.0115</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5252.0116</b>	1	1	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5252.0122</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5252.0123</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5252.0124</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5252.0125</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5252.0126</b>	1	1	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5252.0132</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5252.0133</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5252.0134</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5252.0135</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5252.0136</b>	1	1	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5252.0142</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5252.0143</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5252.0144</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5252.0145</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5252.0146</b>	1	1	0.018 kg
Ring mit LED weiss	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5252.0152</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5252.0153</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5252.0154</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5252.0155</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5252.0156</b>	1	1	0.018 kg

illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
 <p><b>Indicator 19 mm stainless-steel chrome-coloured, Front dimension Ø 22 mm</b></p>									
Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5252.0212</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5252.0213</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5252.0214</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5252.0215</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5252.0216</b>	1	1	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5252.0222</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5252.0223</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5252.0224</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5252.0225</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5252.0226</b>	1	1	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5252.0232</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5252.0233</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5252.0234</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5252.0235</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5252.0236</b>	1	1	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5252.0242</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5252.0243</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5252.0244</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5252.0245</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5252.0246</b>	1	1	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5252.0252</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5252.0253</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5252.0254</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5252.0255</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5252.0256</b>	1	1	0.021 kg
 <p><b>Indicator 19 mm Brass, Front dimension Ø 22 mm</b></p>									
Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5352.0112</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5352.0113</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5352.0114</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5352.0115</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5352.0116</b>	1	1	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5352.0122</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5352.0123</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5352.0124</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5352.0125</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5352.0126</b>	1	1	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5352.0132</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5352.0133</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5352.0134</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5352.0135</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5352.0136</b>	1	1	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5352.0142</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5352.0143</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5352.0144</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5352.0145</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5352.0146</b>	1	1	0.018 kg

# 82 Flush design

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5352.0152</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5352.0153</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5352.0154</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5352.0155</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5352.0156</b>	1	1	0.018 kg



### Indicator 19 mm Brass, Front dimension Ø 22 mm

Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5352.0212</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5352.0213</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5352.0214</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5352.0215</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5352.0216</b>	1	1	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5352.0222</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5352.0223</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5352.0224</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5352.0225</b>	1	1	0.021 kg
Dot with green LED	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5352.0226</b>	1	1	0.021 kg
	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5352.0232</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5352.0233</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5352.0234</b>	1	1	0.021 kg
Dot with yellow LED	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5352.0235</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5352.0236</b>	1	1	0.021 kg
	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5352.0242</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5352.0243</b>	1	1	0.021 kg
Dot with white LED	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5352.0244</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5352.0245</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5352.0246</b>	1	1	0.021 kg
	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5352.0252</b>	1	1	0.021 kg
Dot with white LED	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5352.0253</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5352.0254</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5352.0255</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5352.0256</b>	1	1	0.021 kg



### Indicator 19 mm Aluminium, Front dimension Ø 22 mm

Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5552.0112</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5552.0113</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5552.0114</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5552.0115</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5552.0116</b>	1	1	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5552.0122</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5552.0123</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5552.0124</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5552.0125</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5552.0126</b>	1	1	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5552.0132</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5552.0133</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5552.0134</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5552.0135</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5552.0136</b>	1	1	0.018 kg


illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5552.0142</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5552.0143</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5552.0144</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5552.0145</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5552.0146</b>	1	1	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5552.0152</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5552.0153</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5552.0154</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5552.0155</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5552.0156</b>	1	1	0.018 kg



**Indicator 19 mm Aluminium, Front dimension Ø 22 mm**

Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5552.0212</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5552.0213</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5552.0214</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5552.0215</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5552.0216</b>	1	1	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5552.0222</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5552.0223</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5552.0224</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5552.0225</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5552.0226</b>	1	1	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5552.0232</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5552.0233</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5552.0234</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5552.0235</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5552.0236</b>	1	1	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5552.0242</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5552.0243</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5552.0244</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5552.0245</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5552.0246</b>	1	1	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5552.0252</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5552.0253</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5552.0254</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5552.0255</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5552.0256</b>	1	1	0.021 kg

The component layouts you will find from page 103




# 82 Flush design

Indicator 22 mm, IP 65 & IP 67




Product can differ from the current configuration.




Dimensions [mm]  
L1 = Solder/Plug-in terminal 2.8 x 0.5 mm,  
X = Screw terminal

Equipment consisting of (schematic overview)



Each Part Number listed below includes all the black components shown in the 3D-drawing.



Mounting cut-outs [mm]

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
 <p><b>Indicator 22 mm stainless-steel, Front dimension Ø 25 mm</b></p>									
Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.0112</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.0113</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.0114</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.0115</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.0116</b>	1	1	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.0122</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.0123</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.0124</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.0125</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.0126</b>	1	1	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.0132</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.0133</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.0134</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.0135</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.0136</b>	1	1	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.0142</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.0143</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.0144</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.0145</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.0146</b>	1	1	0.018 kg

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.0152</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.0153</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.0154</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.0155</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.0156</b>	1	1	0.018 kg



**Indicator 22 mm stainless-steel, Front dimension Ø 25 mm**

Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.0212</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.0213</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.0214</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.0215</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.0216</b>	1	1	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.0222</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.0223</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.0224</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.0225</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.0226</b>	1	1	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.0232</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.0233</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.0234</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.0235</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.0236</b>	1	1	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.0242</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.0243</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.0244</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.0245</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.0246</b>	1	1	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.0252</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.0253</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.0254</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.0255</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.0256</b>	1	1	0.021 kg



**Indicator 22 mm stainless-steel chrome-coloured, Front dimension Ø 25 mm**

Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.0112</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.0113</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.0114</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.0115</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.0116</b>	1	1	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.0122</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.0123</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.0124</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.0125</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.0126</b>	1	1	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.0132</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.0133</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.0134</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.0135</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.0136</b>	1	1	0.018 kg

# 82 Flush design

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.0142</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.0143</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.0144</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.0145</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.0146</b>	1	1	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.0152</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.0153</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.0154</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.0155</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.0156</b>	1	1	0.018 kg
 <p><b>Indicator 22 mm stainless-steel chrome-coloured, Front dimension Ø 25 mm</b></p>									
Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.0212</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.0213</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.0214</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.0215</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.0216</b>	1	1	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.0222</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.0223</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.0224</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.0225</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.0226</b>	1	1	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.0232</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.0233</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.0234</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.0235</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.0236</b>	1	1	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.0242</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.0243</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.0244</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.0245</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.0246</b>	1	1	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.0252</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.0253</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.0254</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.0255</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.0256</b>	1	1	0.021 kg

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
 <p><b>Indicator 22 mm Brass, Front dimension Ø 25 mm</b></p>									
Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.0112</b>	1	1	0.018 kg
Ring with red LED	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.0113</b>	1	1	0.018 kg
Ring with red LED	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.0114</b>	1	1	0.018 kg
Ring with red LED	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.0115</b>	1	1	0.018 kg
Ring with red LED	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.0116</b>	1	1	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.0122</b>	1	1	0.018 kg
Ring with blue LED	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.0123</b>	1	1	0.018 kg
Ring with blue LED	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.0124</b>	1	1	0.018 kg
Ring with blue LED	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.0125</b>	1	1	0.018 kg
Ring with blue LED	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.0126</b>	1	1	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.0132</b>	1	1	0.018 kg
Ring with green LED	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.0133</b>	1	1	0.018 kg
Ring with green LED	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.0134</b>	1	1	0.018 kg
Ring with green LED	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.0135</b>	1	1	0.018 kg
Ring with green LED	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.0136</b>	1	1	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.0142</b>	1	1	0.018 kg
Ring with yellow LED	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.0143</b>	1	1	0.018 kg
Ring with yellow LED	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.0144</b>	1	1	0.018 kg
Ring with yellow LED	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.0145</b>	1	1	0.018 kg
Ring with yellow LED	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.0146</b>	1	1	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.0152</b>	1	1	0.018 kg
Ring with white LED	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.0153</b>	1	1	0.018 kg
Ring with white LED	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.0154</b>	1	1	0.018 kg
Ring with white LED	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.0155</b>	1	1	0.018 kg
Ring with white LED	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.0156</b>	1	1	0.018 kg

 <p><b>Indicator 22 mm Brass, Front dimension Ø 25 mm</b></p>									
Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.0212</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.0213</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.0214</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.0215</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.0216</b>	1	1	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.0222</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.0223</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.0224</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.0225</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.0226</b>	1	1	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.0232</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.0233</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.0234</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.0235</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.0236</b>	1	1	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.0242</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.0243</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.0244</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.0245</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.0246</b>	1	1	0.021 kg

# 82 Flush design

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.0252</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.0253</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.0254</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.0255</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.0256</b>	1	1	0.021 kg



### Indicator 22 mm Aluminium, Front dimension Ø 25 mm

Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.0112</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.0113</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.0114</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.0115</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.0116</b>	1	1	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.0122</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.0123</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.0124</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.0125</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.0126</b>	1	1	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.0132</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.0133</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.0134</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.0135</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.0136</b>	1	1	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.0142</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.0143</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.0144</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.0145</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.0146</b>	1	1	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.0152</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.0153</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.0154</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.0155</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.0156</b>	1	1	0.018 kg



### Indicator 22 mm Aluminium, Front dimension Ø 25 mm

Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.0212</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.0213</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.0214</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.0215</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.0216</b>	1	1	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.0222</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.0223</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.0224</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.0225</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.0226</b>	1	1	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.0232</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.0233</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.0234</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.0235</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.0236</b>	1	1	0.021 kg

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.0242</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.0243</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.0244</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.0245</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.0246</b>	1	1	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.0252</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.0253</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.0254</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.0255</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.0256</b>	1	1	0.021 kg



**Indicator 22 mm stainless-steel, Front dimension Ø 25 mm**

Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6152.0112</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6152.0113</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6152.0114</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6152.0115</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6152.0116</b>	1	1	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6152.0122</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6152.0123</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6152.0124</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6152.0125</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6152.0126</b>	1	1	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6152.0132</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6152.0133</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6152.0134</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6152.0135</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6152.0136</b>	1	1	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6152.0142</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6152.0143</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6152.0144</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6152.0145</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6152.0146</b>	1	1	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6152.0152</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6152.0153</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6152.0154</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6152.0155</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6152.0156</b>	1	1	0.018 kg



**Indicator 22 mm stainless-steel, Front dimension Ø 25 mm**

Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6152.0212</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6152.0213</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6152.0214</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6152.0215</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6152.0216</b>	1	1	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6152.0222</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6152.0223</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6152.0224</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6152.0225</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6152.0226</b>	1	1	0.021 kg

# 82 Flush design

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6152.0232</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6152.0233</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6152.0234</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6152.0235</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6152.0236</b>	1	1	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6152.0242</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6152.0243</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6152.0244</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6152.0245</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6152.0246</b>	1	1	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6152.0252</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6152.0253</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6152.0254</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6152.0255</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6152.0256</b>	1	1	0.021 kg
 <p><b>Indicator 22 mm stainless-steel chrome-coloured, Front dimension Ø 25 mm</b></p>									
Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6252.0112</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6252.0113</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6252.0114</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6252.0115</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6252.0116</b>	1	1	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6252.0122</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6252.0123</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6252.0124</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6252.0125</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6252.0126</b>	1	1	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6252.0132</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6252.0133</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6252.0134</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6252.0135</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6252.0136</b>	1	1	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6252.0142</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6252.0143</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6252.0144</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6252.0145</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6252.0146</b>	1	1	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6252.0152</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6252.0153</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6252.0154</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6252.0155</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6252.0156</b>	1	1	0.018 kg

illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
 <p><b>Indicator 22 mm stainless-steel chrome-coloured, Front dimension Ø 25 mm</b></p>									
Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6252.0212</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6252.0213</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6252.0214</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6252.0215</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6252.0216</b>	1	1	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6252.0222</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6252.0223</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6252.0224</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6252.0225</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6252.0226</b>	1	1	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6252.0232</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6252.0233</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6252.0234</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6252.0235</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6252.0236</b>	1	1	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6252.0242</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6252.0243</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6252.0244</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6252.0245</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6252.0246</b>	1	1	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6252.0252</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6252.0253</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6252.0254</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6252.0255</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6252.0256</b>	1	1	0.021 kg
 <p><b>Indicator 22 mm Brass, Front dimension Ø 25 mm</b></p>									
Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6352.0112</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6352.0113</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6352.0114</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6352.0115</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6352.0116</b>	1	1	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6352.0122</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6352.0123</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6352.0124</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6352.0125</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6352.0126</b>	1	1	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6352.0132</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6352.0133</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6352.0134</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6352.0135</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6352.0136</b>	1	1	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6352.0142</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6352.0143</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6352.0144</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6352.0145</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6352.0146</b>	1	1	0.018 kg

# 82 Flush design

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6352.0152</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6352.0153</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6352.0154</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6352.0155</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6352.0156</b>	1	1	0.018 kg



### Indicator 22 mm Brass, Front dimension Ø 25 mm

Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6352.0212</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6352.0213</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6352.0214</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6352.0215</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6352.0216</b>	1	1	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6352.0222</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6352.0223</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6352.0224</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6352.0225</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6352.0226</b>	1	1	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6352.0232</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6352.0233</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6352.0234</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6352.0235</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6352.0236</b>	1	1	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6352.0242</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6352.0243</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6352.0244</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6352.0245</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6352.0246</b>	1	1	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6352.0252</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6352.0253</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6352.0254</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6352.0255</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6352.0256</b>	1	1	0.021 kg



### Indicator 22 mm Aluminium, Front dimension Ø 25 mm

Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6552.0112</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6552.0113</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6552.0114</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6552.0115</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6552.0116</b>	1	1	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6552.0122</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6552.0123</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6552.0124</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6552.0125</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6552.0126</b>	1	1	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6552.0132</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6552.0133</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6552.0134</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6552.0135</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6552.0136</b>	1	1	0.018 kg


Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6552.0142</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6552.0143</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6552.0144</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6552.0145</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6552.0146</b>	1	1	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6552.0152</b>	1	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6552.0153</b>	1	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6552.0154</b>	1	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6552.0155</b>	1	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6552.0156</b>	1	1	0.018 kg



### Indicator 22 mm Aluminium, Front dimension Ø 25 mm

Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6552.0212</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6552.0213</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6552.0214</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6552.0215</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6552.0216</b>	1	1	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6552.0222</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6552.0223</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6552.0224</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6552.0225</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6552.0226</b>	1	1	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6552.0232</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6552.0233</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6552.0234</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6552.0235</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6552.0236</b>	1	1	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6552.0242</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6552.0243</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6552.0244</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6552.0245</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6552.0246</b>	1	1	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6552.0252</b>	1	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6552.0253</b>	1	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6552.0254</b>	1	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6552.0255</b>	1	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6552.0256</b>	1	1	0.021 kg

The component layouts you will find from page 103




# 82 Flush design

## Pushbutton 16 mm, IP 65 & IP 67




Product can differ from the current configuration.



Dimensions [mm]  
L1 = Solder/Plug-in terminal 2.8 x 0.5 mm,  
X = Screw terminal


### Equipment consisting of (schematic overview)



Each Part Number listed below includes all the black components shown in the 3D-drawing.

### Additional Information

- Contacts: 1 chance over (NC/NO)



Mounting cut-outs [mm]

Front ring shape	Lens	Switching action	Terminal	Part No.	Component layout	Wiring diagram	Weight
 <p><b>Pushbutton 16 mm stainless-steel, Front dimension Ø 18 mm</b></p>							
flush	flat / level with front ring	B	Solder 2.8 x 0.5 mm	<b>82-4151.1000</b>	2	1	0.018 kg
		C	Solder 2.8 x 0.5 mm	<b>82-4151.2000</b>	2	2	0.018 kg
 <p><b>Pushbutton 16 mm stainless-steel, Front dimension Ø 18 mm</b></p>							
flush	flat / raised above front ring	B	Solder 2.8 x 0.5 mm	<b>82-4161.1000</b>	2	1	0.020 kg
		C	Solder 2.8 x 0.5 mm	<b>82-4161.2000</b>	2	2	0.020 kg
 <p><b>Pushbutton 16 mm stainless-steel, Front dimension Ø 18 mm</b></p>							
flush	convex / level with front ring	B	Solder 2.8 x 0.5 mm	<b>82-4171.1000</b>	2	1	0.019 kg
		C	Solder 2.8 x 0.5 mm	<b>82-4171.2000</b>	2	2	0.019 kg
raised	convex / raised above front ring	B	Solder 2.8 x 0.5 mm	<b>82-4181.1000</b>	2	1	0.023 kg
		C	Solder 2.8 x 0.5 mm	<b>82-4181.2000</b>	2	2	0.023 kg
 <p><b>Pushbutton 16 mm stainless-steel chrome-coloured, Front dimension Ø 18 mm</b></p>							
flush	flat / level with front ring	B	Solder 2.8 x 0.5 mm	<b>82-4251.1000</b>	2	1	0.018 kg
		C	Solder 2.8 x 0.5 mm	<b>82-4251.2000</b>	2	2	0.018 kg

Front ring shape	Lens	Switching action	Terminal	Part No.	Component layout	Wiring diagram	Weight
 <p><b>Pushbutton 16 mm stainless-steel chrome-coloured, Front dimension Ø 18 mm</b></p>							
flush	flat / raised above front ring	B	Solder 2.8 x 0.5 mm	<b>82-4261.1000</b>	2	1	0.020 kg
		C	Solder 2.8 x 0.5 mm	<b>82-4261.2000</b>	2	2	0.020 kg
 <p><b>Pushbutton 16 mm stainless-steel chrome-coloured, Front dimension Ø 18 mm</b></p>							
flush	convex / level with front ring	B	Solder 2.8 x 0.5 mm	<b>82-4271.1000</b>	2	1	0.019 kg
		C	Solder 2.8 x 0.5 mm	<b>82-4271.2000</b>	2	2	0.019 kg
raised	convex / raised above front ring	B	Solder 2.8 x 0.5 mm	<b>82-4281.1000</b>	2	1	0.023 kg
		C	Solder 2.8 x 0.5 mm	<b>82-4281.2000</b>	2	2	0.023 kg
 <p><b>Pushbutton 16 mm Brass, Front dimension Ø 18 mm</b></p>							
flush	flat / level with front ring	B	Solder 2.8 x 0.5 mm	<b>82-4351.1000</b>	2	1	0.018 kg
		C	Solder 2.8 x 0.5 mm	<b>82-4351.2000</b>	2	2	0.018 kg
 <p><b>Pushbutton 16 mm Brass, Front dimension Ø 18 mm</b></p>							
flush	flat / raised above front ring	B	Solder 2.8 x 0.5 mm	<b>82-4361.1000</b>	2	1	0.020 kg
		C	Solder 2.8 x 0.5 mm	<b>82-4361.2000</b>	2	2	0.020 kg
 <p><b>Pushbutton 16 mm Brass, Front dimension Ø 18 mm</b></p>							
flush	convex / level with front ring	B	Solder 2.8 x 0.5 mm	<b>82-4371.1000</b>	2	1	0.019 kg
		C	Solder 2.8 x 0.5 mm	<b>82-4371.2000</b>	2	2	0.019 kg
raised	convex / raised above front ring	B	Solder 2.8 x 0.5 mm	<b>82-4381.1000</b>	2	1	0.023 kg
		C	Solder 2.8 x 0.5 mm	<b>82-4381.2000</b>	2	2	0.023 kg
 <p><b>Pushbutton 16 mm Aluminium, Front dimension Ø 18 mm</b></p>							
flush	flat / level with front ring	B	Solder 2.8 x 0.5 mm	<b>82-4551.1000</b>	2	1	0.018 kg
		C	Solder 2.8 x 0.5 mm	<b>82-4551.2000</b>	2	2	0.018 kg
 <p><b>Pushbutton 16 mm Aluminium, Front dimension Ø 18 mm</b></p>							
flush	flat / raised above front ring	B	Solder 2.8 x 0.5 mm	<b>82-4561.1000</b>	2	1	0.020 kg
		C	Solder 2.8 x 0.5 mm	<b>82-4561.2000</b>	2	2	0.020 kg
Front ring shape	Lens	Switching action	Terminal	Part No.	Component layout	Wiring diagram	Weight

# 82 Flush design



## Pushbutton 16 mm Aluminium, Front dimension Ø 18 mm

flush	convex / level with front ring	B	Solder 2.8 x 0.5 mm	<b>82-4571.1000</b>	2	1	0.019 kg
		C	Solder 2.8 x 0.5 mm	<b>82-4571.2000</b>	2	2	0.019 kg
raised	convex / raised above front ring	B	Solder 2.8 x 0.5 mm	<b>82-4581.1000</b>	2	1	0.023 kg
		C	Solder 2.8 x 0.5 mm	<b>82-4581.2000</b>	2	2	0.023 kg



## Pushbutton 16 mm stainless-steel, Front dimension Ø 18 mm

flush	flat / level with front ring	B	Screw	<b>82-4152.1000</b>	2	1	0.018 kg
		C	Screw	<b>82-4152.2000</b>	2	2	0.018 kg



## Pushbutton 16 mm stainless-steel, Front dimension Ø 18 mm

flush	flat / raised above front ring	B	Screw	<b>82-4162.1000</b>	2	1	0.020 kg
		C	Screw	<b>82-4162.2000</b>	2	2	0.020 kg



## Pushbutton 16 mm stainless-steel, Front dimension Ø 18 mm

flush	convex / level with front ring	B	Screw	<b>82-4172.1000</b>	2	1	0.019 kg
		C	Screw	<b>82-4172.2000</b>	2	2	0.019 kg
raised	convex / raised above front ring	B	Screw	<b>82-4182.1000</b>	2	1	0.023 kg
		C	Screw	<b>82-4182.2000</b>	2	2	0.023 kg



## Pushbutton 16 mm stainless-steel chrome-coloured, Front dimension Ø 18 mm

flush	flat / level with front ring	B	Screw	<b>82-4252.1000</b>	2	1	0.018 kg
		C	Screw	<b>82-4252.2000</b>	2	2	0.018 kg



## Pushbutton 16 mm stainless-steel chrome-coloured, Front dimension Ø 18 mm

flush	flat / raised above front ring	B	Screw	<b>82-4262.1000</b>	2	1	0.020 kg
		C	Screw	<b>82-4262.2000</b>	2	2	0.020 kg




## Pushbutton 16 mm stainless-steel chrome-coloured, Front dimension Ø 18 mm

flush	convex / level with front ring	B	Screw	<b>82-4272.1000</b>	2	1	0.019 kg
		C	Screw	<b>82-4272.2000</b>	2	2	0.019 kg
raised	convex / raised above front ring	B	Screw	<b>82-4282.1000</b>	2	1	0.023 kg
		C	Screw	<b>82-4282.2000</b>	2	2	0.023 kg

<b>Front ring shape</b>	<b>Lens</b>	<b>Switching action</b>	<b>Terminal</b>	<b>Part No.</b>	<b>Component layout</b>	<b>Wiring diagram</b>	<b>Weight</b>
-------------------------	-------------	-------------------------	-----------------	-----------------	-------------------------	-----------------------	---------------

 <p><b>Pushbutton 16 mm Brass, Front dimension Ø 18 mm</b></p>							
flush	flat / level with front ring	B	Screw	<b>82-4352.1000</b>	2	1	0.018 kg
		C	Screw	<b>82-4352.2000</b>	2	2	0.018 kg
 <p><b>Pushbutton 16 mm Brass, Front dimension Ø 18 mm</b></p>							
flush	flat / raised above front ring	B	Screw	<b>82-4362.1000</b>	2	1	0.020 kg
		C	Screw	<b>82-4362.2000</b>	2	2	0.020 kg
 <p><b>Pushbutton 16 mm Brass, Front dimension Ø 18 mm</b></p>							
flush	convex / level with front ring	B	Screw	<b>82-4372.1000</b>	2	1	0.019 kg
		C	Screw	<b>82-4372.2000</b>	2	2	0.019 kg
raised	convex / raised above front ring	B	Screw	<b>82-4382.1000</b>	2	1	0.023 kg
		C	Screw	<b>82-4382.2000</b>	2	2	0.023 kg
 <p><b>Pushbutton 16 mm Aluminium, Front dimension Ø 18 mm</b></p>							
flush	flat / level with front ring	B	Screw	<b>82-4552.1000</b>	2	1	0.018 kg
		C	Screw	<b>82-4552.2000</b>	2	2	0.018 kg
 <p><b>Pushbutton 16 mm Aluminium, Front dimension Ø 18 mm</b></p>							
flush	flat / raised above front ring	B	Screw	<b>82-4562.1000</b>	2	1	0.020 kg
		C	Screw	<b>82-4562.2000</b>	2	2	0.020 kg
 <p><b>Pushbutton 16 mm Aluminium, Front dimension Ø 18 mm</b></p>							
flush	convex / level with front ring	B	Screw	<b>82-4572.1000</b>	2	1	0.019 kg
		C	Screw	<b>82-4572.2000</b>	2	2	0.019 kg
raised	convex / raised above front ring	B	Screw	<b>82-4582.1000</b>	2	1	0.023 kg
		C	Screw	<b>82-4582.2000</b>	2	2	0.023 kg

Switching action: B = Momentary, C = Maintained  
 The component layouts you will find from page 103




# 82 Flush design

## Pushbutton 19 mm, IP 65 & IP 67




Product can differ from the current configuration.



Dimensions [mm]  
L1 = Solder/Plug-in terminal 2.8 x 0.5 mm,  
X = Screw terminal


### Equipment consisting of (schematic overview)



Each Part Number listed below includes all the black components shown in the 3D-drawing.

### Additional Information

- Contacts: 1 chance over (NC/NO)



Mounting cut-outs [mm]

Front ring shape	Lens	Switching action	Terminal	Part No.	Component layout	Wiring diagram	Weight
 <p><b>Pushbutton 19 mm stainless-steel, Front dimension Ø 22 mm</b></p>							
flush	flat / level with front ring	B	Solder 2.8 x 0.5 mm	<b>82-5151.1000</b>	2	1	0.018 kg
		C	Solder 2.8 x 0.5 mm	<b>82-5151.2000</b>	2	2	0.018 kg
 <p><b>Pushbutton 19 mm stainless-steel, Front dimension Ø 22 mm</b></p>							
flush	flat / raised above front ring	B	Solder 2.8 x 0.5 mm	<b>82-5161.1000</b>	2	1	0.020 kg
		C	Solder 2.8 x 0.5 mm	<b>82-5161.2000</b>	2	2	0.020 kg
 <p><b>Pushbutton 19 mm stainless-steel, Front dimension Ø 22 mm</b></p>							
flush	convex / level with front ring	B	Solder 2.8 x 0.5 mm	<b>82-5171.1000</b>	2	1	0.019 kg
		C	Solder 2.8 x 0.5 mm	<b>82-5171.2000</b>	2	2	0.019 kg
raised	convex / raised above front ring	B	Solder 2.8 x 0.5 mm	<b>82-5181.1000</b>	2	1	0.023 kg
		C	Solder 2.8 x 0.5 mm	<b>82-5181.2000</b>	2	2	0.023 kg
 <p><b>Pushbutton 19 mm stainless-steel chrome-coloured, Front dimension Ø 22 mm</b></p>							
flush	flat / level with front ring	B	Solder 2.8 x 0.5 mm	<b>82-5251.1000</b>	2	1	0.018 kg
		C	Solder 2.8 x 0.5 mm	<b>82-5251.2000</b>	2	2	0.018 kg


Front ring shape	Lens	Switching action	Terminal	Part No.	Component layout	Wiring diagram	Weight
 <p><b>Pushbutton 19 mm stainless-steel chrome-coloured, Front dimension Ø 22 mm</b></p>							
flush	flat / raised above front ring	B	Solder 2.8 x 0.5 mm	<b>82-5261.1000</b>	2	1	0.020 kg
		C	Solder 2.8 x 0.5 mm	<b>82-5261.2000</b>	2	2	0.020 kg
 <p><b>Pushbutton 19 mm stainless-steel chrome-coloured, Front dimension Ø 22 mm</b></p>							
flush	convex / level with front ring	B	Solder 2.8 x 0.5 mm	<b>82-5271.1000</b>	2	1	0.019 kg
		C	Solder 2.8 x 0.5 mm	<b>82-5271.2000</b>	2	2	0.019 kg
raised	convex / raised above front ring	B	Solder 2.8 x 0.5 mm	<b>82-5281.1000</b>	2	1	0.023 kg
		C	Solder 2.8 x 0.5 mm	<b>82-5281.2000</b>	2	2	0.023 kg
 <p><b>Pushbutton 19 mm Brass, Front dimension Ø 22 mm</b></p>							
flush	flat / level with front ring	B	Solder 2.8 x 0.5 mm	<b>82-5351.1000</b>	2	1	0.018 kg
		C	Solder 2.8 x 0.5 mm	<b>82-5351.2000</b>	2	2	0.018 kg
 <p><b>Pushbutton 19 mm Brass, Front dimension Ø 22 mm</b></p>							
flush	flat / raised above front ring	B	Solder 2.8 x 0.5 mm	<b>82-5361.1000</b>	2	1	0.020 kg
		C	Solder 2.8 x 0.5 mm	<b>82-5361.2000</b>	2	2	0.020 kg
 <p><b>Pushbutton 19 mm Brass, Front dimension Ø 22 mm</b></p>							
flush	convex / level with front ring	B	Solder 2.8 x 0.5 mm	<b>82-5371.1000</b>	2	1	0.019 kg
		C	Solder 2.8 x 0.5 mm	<b>82-5371.2000</b>	2	2	0.019 kg
raised	convex / raised above front ring	B	Solder 2.8 x 0.5 mm	<b>82-5381.1000</b>	2	1	0.023 kg
		C	Solder 2.8 x 0.5 mm	<b>82-5381.2000</b>	2	2	0.023 kg
 <p><b>Pushbutton 19 mm Aluminium, Front dimension Ø 22 mm</b></p>							
flush	flat / level with front ring	B	Solder 2.8 x 0.5 mm	<b>82-5551.1000</b>	2	1	0.018 kg
		C	Solder 2.8 x 0.5 mm	<b>82-5551.2000</b>	2	2	0.018 kg
 <p><b>Pushbutton 19 mm Aluminium, Front dimension Ø 22 mm</b></p>							
flush	flat / raised above front ring	B	Solder 2.8 x 0.5 mm	<b>82-5561.1000</b>	2	1	0.020 kg
		C	Solder 2.8 x 0.5 mm	<b>82-5561.2000</b>	2	2	0.020 kg

# 82 Flush design

Front ring shape	Lens	Switching action	Terminal	Part No.	Component layout	Wiring diagram	Weight
 <p><b>Pushbutton 19 mm Aluminium, Front dimension Ø 22 mm</b></p>							
flush	convex / level with front ring	B	Solder 2.8 x 0.5 mm	<b>82-5571.1000</b>	2	1	0.019 kg
		C	Solder 2.8 x 0.5 mm	<b>82-5571.2000</b>	2	2	0.019 kg
raised	convex / raised above front ring	B	Solder 2.8 x 0.5 mm	<b>82-5581.1000</b>	2	1	0.023 kg
		C	Solder 2.8 x 0.5 mm	<b>82-5581.2000</b>	2	2	0.023 kg
 <p><b>Pushbutton 19 mm stainless-steel, Front dimension Ø 22 mm</b></p>							
flush	flat / level with front ring	B	Screw	<b>82-5152.1000</b>	2	1	0.018 kg
		C	Screw	<b>82-5152.2000</b>	2	2	0.018 kg
 <p><b>Pushbutton 19 mm stainless-steel, Front dimension Ø 22 mm</b></p>							
flush	flat / raised above front ring	B	Screw	<b>82-5162.1000</b>	2	1	0.020 kg
		C	Screw	<b>82-5162.2000</b>	2	2	0.020 kg
 <p><b>Pushbutton 19 mm stainless-steel, Front dimension Ø 22 mm</b></p>							
flush	convex / level with front ring	B	Screw	<b>82-5172.1000</b>	2	1	0.019 kg
		C	Screw	<b>82-5172.2000</b>	2	2	0.019 kg
raised	convex / raised above front ring	B	Screw	<b>82-5182.1000</b>	2	1	0.023 kg
		C	Screw	<b>82-5182.2000</b>	2	2	0.023 kg
 <p><b>Pushbutton 19 mm stainless-steel chrome-coloured, Front dimension Ø 22 mm</b></p>							
flush	flat / level with front ring	B	Screw	<b>82-5252.1000</b>	2	1	0.018 kg
		C	Screw	<b>82-5252.2000</b>	2	2	0.018 kg
 <p><b>Pushbutton 19 mm stainless-steel chrome-coloured, Front dimension Ø 22 mm</b></p>							
flush	flat / raised above front ring	B	Screw	<b>82-5262.1000</b>	2	1	0.020 kg
		C	Screw	<b>82-5262.2000</b>	2	2	0.020 kg
 <p><b>Pushbutton 19 mm stainless-steel chrome-coloured, Front dimension Ø 22 mm</b></p>							
flush	convex / level with front ring	B	Screw	<b>82-5272.1000</b>	2	1	0.019 kg
		C	Screw	<b>82-5272.2000</b>	2	2	0.019 kg
raised	convex / raised above front ring	B	Screw	<b>82-5282.1000</b>	2	1	0.023 kg
		C	Screw	<b>82-5282.2000</b>	2	2	0.023 kg

Front ring shape	Lens	Switching action	Terminal	Part No.	Component layout	Wiring diagram	Weight
 <p><b>Pushbutton 19 mm Brass, Front dimension Ø 22 mm</b></p>							
flush	flat / level with front ring	B	Screw	<b>82-5352.1000</b>	2	1	0.018 kg
		C	Screw	<b>82-5352.2000</b>	2	2	0.018 kg
 <p><b>Pushbutton 19 mm Brass, Front dimension Ø 22 mm</b></p>							
flush	flat / raised above front ring	B	Screw	<b>82-5362.1000</b>	2	1	0.020 kg
		C	Screw	<b>82-5362.2000</b>	2	2	0.020 kg
 <p><b>Pushbutton 19 mm Brass, Front dimension Ø 22 mm</b></p>							
flush	convex / level with front ring	B	Screw	<b>82-5372.1000</b>	2	1	0.019 kg
		C	Screw	<b>82-5372.2000</b>	2	2	0.019 kg
raised	convex / raised above front ring	B	Screw	<b>82-5382.1000</b>	2	1	0.023 kg
		C	Screw	<b>82-5382.2000</b>	2	2	0.023 kg
 <p><b>Pushbutton 19 mm Aluminium, Front dimension Ø 22 mm</b></p>							
flush	flat / level with front ring	B	Screw	<b>82-5552.1000</b>	2	1	0.018 kg
		C	Screw	<b>82-5552.2000</b>	2	2	0.018 kg
 <p><b>Pushbutton 19 mm Aluminium, Front dimension Ø 22 mm</b></p>							
flush	flat / raised above front ring	B	Screw	<b>82-5562.1000</b>	2	1	0.020 kg
		C	Screw	<b>82-5562.2000</b>	2	2	0.020 kg
 <p><b>Pushbutton 19 mm Aluminium, Front dimension Ø 22 mm</b></p>							
flush	convex / level with front ring	B	Screw	<b>82-5572.1000</b>	2	1	0.019 kg
		C	Screw	<b>82-5572.2000</b>	2	2	0.019 kg
raised	convex / raised above front ring	B	Screw	<b>82-5582.1000</b>	2	1	0.023 kg
		C	Screw	<b>82-5582.2000</b>	2	2	0.023 kg

Switching action: B = Momentary, C = Maintained  
 The component layouts you will find from page 103




# 82 Flush design

## Pushbutton 22 mm, IP 65 & IP 67




Product can differ from the current configuration.




Dimensions [mm]  
L1 = Solder/Plug-in terminal 2.8 x 0.5 mm,  
X = Screw terminal

### Equipment consisting of (schematic overview)



### Additional Information

- Contacts: 1 chance over (NC/NO)



Mounting cut-outs [mm]

Each Part Number listed below includes all the black components shown in the 3D-drawing.

Front ring shape	Lens	Switching action	Terminal	Part No.	Component layout	Wiring diagram	Weight
 <p><b>Pushbutton 22 mm stainless-steel, Front dimension Ø 25 mm</b></p>							
flush	flat / level with front ring	B	Solder 2.8 x 0.5 mm	<b>82-6151.1000</b>	2	1	0.018 kg
		C	Solder 2.8 x 0.5 mm	<b>82-6151.2000</b>	2	2	0.018 kg
 <p><b>Pushbutton 22 mm stainless-steel, Front dimension Ø 25 mm</b></p>							
flush	flat / raised above front ring	B	Solder 2.8 x 0.5 mm	<b>82-6161.1000</b>	2	1	0.020 kg
		C	Solder 2.8 x 0.5 mm	<b>82-6161.2000</b>	2	2	0.020 kg
 <p><b>Pushbutton 22 mm stainless-steel, Front dimension Ø 25 mm</b></p>							
flush	convex / level with front ring	B	Solder 2.8 x 0.5 mm	<b>82-6171.1000</b>	2	1	0.019 kg
		C	Solder 2.8 x 0.5 mm	<b>82-6171.2000</b>	2	2	0.019 kg
raised	convex / raised above front ring	B	Solder 2.8 x 0.5 mm	<b>82-6181.1000</b>	2	1	0.023 kg
		C	Solder 2.8 x 0.5 mm	<b>82-6181.2000</b>	2	2	0.023 kg
 <p><b>Pushbutton 22 mm stainless-steel chrome-coloured, Front dimension Ø 25 mm</b></p>							
flush	flat / level with front ring	B	Solder 2.8 x 0.5 mm	<b>82-6251.1000</b>	2	1	0.018 kg
		C	Solder 2.8 x 0.5 mm	<b>82-6251.2000</b>	2	2	0.018 kg


Front ring shape	Lens	Switching action	Terminal	Part No.	Component layout	Wiring diagram	Weight
 <p><b>Pushbutton 22 mm stainless-steel chrome-coloured, Front dimension Ø 25 mm</b></p>							
flush	flat / raised above front ring	B	Solder 2.8 x 0.5 mm	<b>82-6261.1000</b>	2	1	0.020 kg
		C	Solder 2.8 x 0.5 mm	<b>82-6261.2000</b>	2	2	0.020 kg
 <p><b>Pushbutton 22 mm stainless-steel chrome-coloured, Front dimension Ø 25 mm</b></p>							
flush	convex / level with front ring	B	Solder 2.8 x 0.5 mm	<b>82-6271.1000</b>	2	1	0.019 kg
		C	Solder 2.8 x 0.5 mm	<b>82-6271.2000</b>	2	2	0.019 kg
raised	convex / raised above front ring	B	Solder 2.8 x 0.5 mm	<b>82-6281.1000</b>	2	1	0.023 kg
		C	Solder 2.8 x 0.5 mm	<b>82-6281.2000</b>	2	2	0.023 kg
 <p><b>Pushbutton 22 mm Brass, Front dimension Ø 25 mm</b></p>							
flush	flat / level with front ring	B	Solder 2.8 x 0.5 mm	<b>82-6351.1000</b>	2	1	0.018 kg
		C	Solder 2.8 x 0.5 mm	<b>82-6351.2000</b>	2	2	0.018 kg
 <p><b>Pushbutton 22 mm Brass, Front dimension Ø 25 mm</b></p>							
flush	flat / raised above front ring	B	Solder 2.8 x 0.5 mm	<b>82-6361.1000</b>	2	1	0.020 kg
		C	Solder 2.8 x 0.5 mm	<b>82-6361.2000</b>	2	2	0.020 kg
 <p><b>Pushbutton 22 mm Brass, Front dimension Ø 25 mm</b></p>							
flush	convex / level with front ring	B	Solder 2.8 x 0.5 mm	<b>82-6371.1000</b>	2	1	0.019 kg
		C	Solder 2.8 x 0.5 mm	<b>82-6371.2000</b>	2	2	0.019 kg
raised	convex / raised above front ring	B	Solder 2.8 x 0.5 mm	<b>82-6381.1000</b>	2	1	0.023 kg
		C	Solder 2.8 x 0.5 mm	<b>82-6381.2000</b>	2	2	0.023 kg
 <p><b>Pushbutton 22 mm Aluminium, Front dimension Ø 25 mm</b></p>							
flush	flat / level with front ring	B	Solder 2.8 x 0.5 mm	<b>82-6551.1000</b>	2	1	0.018 kg
		C	Solder 2.8 x 0.5 mm	<b>82-6551.2000</b>	2	2	0.018 kg
 <p><b>Pushbutton 22 mm Aluminium, Front dimension Ø 25 mm</b></p>							
flush	flat / raised above front ring	B	Solder 2.8 x 0.5 mm	<b>82-6561.1000</b>	2	1	0.020 kg
		C	Solder 2.8 x 0.5 mm	<b>82-6561.2000</b>	2	2	0.020 kg

# 82 Flush design

Front ring shape	Lens	Switching action	Terminal	Part No.	Component layout	Wiring diagram	Weight
 <p><b>Pushbutton 22 mm Aluminium, Front dimension Ø 25 mm</b></p>							
flush	convex / level with front ring	B	Solder 2.8 x 0.5 mm	<b>82-6571.1000</b>	2	1	0.019 kg
		C	Solder 2.8 x 0.5 mm	<b>82-6571.2000</b>	2	2	0.019 kg
raised	convex / raised above front ring	B	Solder 2.8 x 0.5 mm	<b>82-6581.1000</b>	2	1	0.023 kg
		C	Solder 2.8 x 0.5 mm	<b>82-6581.2000</b>	2	2	0.023 kg
 <p><b>Pushbutton 22 mm stainless-steel, Front dimension Ø 25 mm</b></p>							
flush	flat / level with front ring	B	Screw	<b>82-6152.1000</b>	2	1	0.018 kg
		C	Screw	<b>82-6152.2000</b>	2	2	0.018 kg
 <p><b>Pushbutton 22 mm stainless-steel, Front dimension Ø 25 mm</b></p>							
flush	flat / raised above front ring	B	Screw	<b>82-6162.1000</b>	2	1	0.020 kg
		C	Screw	<b>82-6162.2000</b>	2	2	0.020 kg
 <p><b>Pushbutton 22 mm stainless-steel, Front dimension Ø 25 mm</b></p>							
flush	convex / level with front ring	B	Screw	<b>82-6172.1000</b>	2	1	0.019 kg
		C	Screw	<b>82-6172.2000</b>	2	2	0.019 kg
raised	convex / raised above front ring	B	Screw	<b>82-6182.1000</b>	2	1	0.023 kg
		C	Screw	<b>82-6182.2000</b>	2	2	0.023 kg
 <p><b>Pushbutton 22 mm stainless-steel chrome-coloured, Front dimension Ø 25 mm</b></p>							
flush	flat / level with front ring	B	Screw	<b>82-6252.1000</b>	2	1	0.018 kg
		C	Screw	<b>82-6252.2000</b>	2	2	0.018 kg
 <p><b>Pushbutton 22 mm stainless-steel chrome-coloured, Front dimension Ø 25 mm</b></p>							
flush	flat / raised above front ring	B	Screw	<b>82-6262.1000</b>	2	1	0.020 kg
		C	Screw	<b>82-6262.2000</b>	2	2	0.020 kg
 <p><b>Pushbutton 22 mm stainless-steel chrome-coloured, Front dimension Ø 25 mm</b></p>							
flush	convex / level with front ring	B	Screw	<b>82-6272.1000</b>	2	1	0.019 kg
		C	Screw	<b>82-6272.2000</b>	2	2	0.019 kg
raised	convex / raised above front ring	B	Screw	<b>82-6282.1000</b>	2	1	0.023 kg
		C	Screw	<b>82-6282.2000</b>	2	2	0.023 kg

Front ring shape	Lens	Switching action	Terminal	Part No.	Component layout	Wiring diagram	Weight
 <p><b>Pushbutton 22 mm Brass, Front dimension Ø 25 mm</b></p>							
flush	flat / level with front ring	B	Screw	<b>82-6352.1000</b>	2	1	0.018 kg
		C	Screw	<b>82-6352.2000</b>	2	2	0.018 kg
 <p><b>Pushbutton 22 mm Brass, Front dimension Ø 25 mm</b></p>							
flush	flat / raised above front ring	B	Screw	<b>82-6362.1000</b>	2	1	0.020 kg
		C	Screw	<b>82-6362.2000</b>	2	2	0.020 kg
 <p><b>Pushbutton 22 mm Brass, Front dimension Ø 25 mm</b></p>							
flush	convex / level with front ring	B	Screw	<b>82-6372.1000</b>	2	1	0.019 kg
		C	Screw	<b>82-6372.2000</b>	2	2	0.019 kg
raised	convex / raised above front ring	B	Screw	<b>82-6382.1000</b>	2	1	0.023 kg
		C	Screw	<b>82-6382.2000</b>	2	2	0.023 kg
 <p><b>Pushbutton 22 mm Aluminium, Front dimension Ø 25 mm</b></p>							
flush	flat / level with front ring	B	Screw	<b>82-6552.1000</b>	2	1	0.018 kg
		C	Screw	<b>82-6552.2000</b>	2	2	0.018 kg
 <p><b>Pushbutton 22 mm Aluminium, Front dimension Ø 25 mm</b></p>							
flush	flat / raised above front ring	B	Screw	<b>82-6562.1000</b>	2	1	0.020 kg
		C	Screw	<b>82-6562.2000</b>	2	2	0.020 kg
 <p><b>Pushbutton 22 mm Aluminium, Front dimension Ø 25 mm</b></p>							
flush	convex / level with front ring	B	Screw	<b>82-6572.1000</b>	2	1	0.019 kg
		C	Screw	<b>82-6572.2000</b>	2	2	0.019 kg
raised	convex / raised above front ring	B	Screw	<b>82-6582.1000</b>	2	1	0.023 kg
		C	Screw	<b>82-6582.2000</b>	2	2	0.023 kg

Switching action: B = Momentary, C = Maintained  
 The component layouts you will find from page 103




# 82 Flush design

## Illuminated pushbutton 16 mm, IP 65 & IP 67




Product can differ from the current configuration.




Dimensions [mm]  
L1 = Solder/Plug-in terminal 2.8 x 0.5 mm,  
X = Screw terminal

### Equipment consisting of (schematic overview)



### Additional Information

- Contacts: 1 chance over (NC/NO)



Mounting cut-outs [mm]

Each Part Number listed below includes all the black components shown in the 3D-drawing.

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
 <p><b>Illuminated pushbutton 16 mm stainless-steel, momentary, Front dimension Ø 18 mm</b></p>									
Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.1112</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.1113</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.1114</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.1115</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.1116</b>	3	1	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.1122</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.1123</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.1124</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.1125</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.1126</b>	3	1	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.1132</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.1133</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.1134</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.1135</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.1136</b>	3	1	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.1142</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.1143</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.1144</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.1145</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.1146</b>	3	1	0.018 kg

illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.1152</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.1153</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.1154</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.1155</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.1156</b>	3	1	0.018 kg



**Illuminated pushbutton 16 mm stainless-steel, momentary, Front dimension Ø 18 mm**

Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.1212</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.1213</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.1214</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.1215</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.1216</b>	3	1	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.1222</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.1223</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.1224</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.1225</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.1226</b>	3	1	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.1232</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.1233</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.1234</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.1235</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.1236</b>	3	1	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.1242</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.1243</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.1244</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.1245</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.1246</b>	3	1	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.1252</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.1253</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.1254</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.1255</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.1256</b>	3	1	0.021 kg



**Illuminated pushbutton 16 mm stainless-steel, maintain, Front dimension Ø 18 mm**

Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.2112</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.2113</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.2114</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.2115</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.2116</b>	3	2	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.2122</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.2123</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.2124</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.2125</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.2126</b>	3	2	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.2132</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.2133</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.2134</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.2135</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.2136</b>	3	2	0.018 kg

# 82 Flush design

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.2142</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.2143</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.2144</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.2145</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.2146</b>	3	2	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.2152</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.2153</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.2154</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.2155</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.2156</b>	3	2	0.018 kg



## Illuminated pushbutton 16 mm stainless-steel, maintain, Front dimension Ø 18 mm

Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.2212</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.2213</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.2214</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.2215</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.2216</b>	3	2	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.2222</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.2223</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.2224</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.2225</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.2226</b>	3	2	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.2232</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.2233</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.2234</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.2235</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.2236</b>	3	2	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.2242</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.2243</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.2244</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.2245</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.2246</b>	3	2	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.2252</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.2253</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.2254</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.2255</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4151.2256</b>	3	2	0.021 kg



## Illuminated pushbutton 16 mm stainless-steel chrome-coloured, momentary, Front dimension Ø 18 mm

Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.1112</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.1113</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.1114</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.1115</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.1116</b>	3	1	0.018 kg

illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.1122</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.1123</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.1124</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.1125</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.1126</b>	3	1	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.1132</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.1133</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.1134</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.1135</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.1136</b>	3	1	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.1142</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.1143</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.1144</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.1145</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.1146</b>	3	1	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.1152</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.1153</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.1154</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.1155</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.1156</b>	3	1	0.018 kg



**Illuminated pushbutton 16 mm stainless-steel chrome-coloured, momentary, Front dimension Ø 18 mm**

Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.1212</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.1213</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.1214</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.1215</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.1216</b>	3	1	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.1222</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.1223</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.1224</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.1225</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.1226</b>	3	1	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.1232</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.1233</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.1234</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.1235</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.1236</b>	3	1	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.1242</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.1243</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.1244</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.1245</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.1246</b>	3	1	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.1252</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.1253</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.1254</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.1255</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.1256</b>	3	1	0.021 kg

# 82 Flush design

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
 <p><b>Illuminated pushbutton 16 mm stainless-steel chrome-coloured, maintain, Front dimension Ø 18 mm</b></p>									
Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.2112</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.2113</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.2114</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.2115</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.2116</b>	3	2	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.2122</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.2123</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.2124</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.2125</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.2126</b>	3	2	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.2132</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.2133</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.2134</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.2135</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.2136</b>	3	2	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.2142</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.2143</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.2144</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.2145</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.2146</b>	3	2	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.2152</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.2153</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.2154</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.2155</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.2156</b>	3	2	0.018 kg
 <p><b>Illuminated pushbutton 16 mm stainless-steel chrome-coloured, maintain, Front dimension Ø 18 mm</b></p>									
Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.2212</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.2213</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.2214</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.2215</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.2216</b>	3	2	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.2222</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.2223</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.2224</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.2225</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.2226</b>	3	2	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.2232</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.2233</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.2234</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.2235</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.2236</b>	3	2	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.2242</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.2243</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.2244</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.2245</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.2246</b>	3	2	0.021 kg

illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.2252</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.2253</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.2254</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.2255</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4251.2256</b>	3	2	0.021 kg



**Illuminated pushbutton 16 mm Brass, momentary, Front dimension Ø 18 mm**

Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.1112</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.1113</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.1114</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.1115</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.1116</b>	3	1	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.1122</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.1123</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.1124</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.1125</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.1126</b>	3	1	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.1132</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.1133</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.1134</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.1135</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.1136</b>	3	1	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.1142</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.1143</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.1144</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.1145</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.1146</b>	3	1	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.1152</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.1153</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.1154</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.1155</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.1156</b>	3	1	0.018 kg



**Illuminated pushbutton 16 mm Brass, momentary, Front dimension Ø 18 mm**

Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.1212</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.1213</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.1214</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.1215</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.1216</b>	3	1	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.1222</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.1223</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.1224</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.1225</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.1226</b>	3	1	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.1232</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.1233</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.1234</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.1235</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.1236</b>	3	1	0.021 kg

# 82 Flush design

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.1242</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.1243</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.1244</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.1245</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.1246</b>	3	1	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.1252</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.1253</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.1254</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.1255</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.1256</b>	3	1	0.021 kg



### Illuminated pushbutton 16 mm Brass, maintain, Front dimension Ø 18 mm

Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.2112</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.2113</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.2114</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.2115</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.2116</b>	3	2	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.2122</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.2123</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.2124</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.2125</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.2126</b>	3	2	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.2132</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.2133</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.2134</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.2135</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.2136</b>	3	2	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.2142</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.2143</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.2144</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.2145</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.2146</b>	3	2	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.2152</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.2153</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.2154</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.2155</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.2156</b>	3	2	0.018 kg



### Illuminated pushbutton 16 mm Brass, maintain, Front dimension Ø 18 mm

Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.2212</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.2213</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.2214</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.2215</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.2216</b>	3	2	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.2222</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.2223</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.2224</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.2225</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.2226</b>	3	2	0.021 kg

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.2232</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.2233</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.2234</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.2235</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.2236</b>	3	2	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.2242</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.2243</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.2244</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.2245</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.2246</b>	3	2	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.2252</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.2253</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.2254</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.2255</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4351.2256</b>	3	2	0.021 kg



**Illuminated pushbutton 16 mm Aluminium, momentary, Front dimension Ø 18 mm**

Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.1112</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.1113</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.1114</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.1115</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.1116</b>	3	1	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.1122</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.1123</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.1124</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.1125</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.1126</b>	3	1	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.1132</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.1133</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.1134</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.1135</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.1136</b>	3	1	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.1142</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.1143</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.1144</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.1145</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.1146</b>	3	1	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.1152</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.1153</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.1154</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.1155</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.1156</b>	3	1	0.018 kg

# 82 Flush design

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
									
<b>Illuminated pushbutton 16 mm Aluminium, momentary, Front dimension Ø 18 mm</b>									
Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.1212</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.1213</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.1214</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.1215</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.1216</b>	3	1	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.1222</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.1223</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.1224</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.1225</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.1226</b>	3	1	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.1232</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.1233</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.1234</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.1235</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.1236</b>	3	1	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.1242</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.1243</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.1244</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.1245</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.1246</b>	3	1	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.1252</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.1253</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.1254</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.1255</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.1256</b>	3	1	0.021 kg
									
<b>Illuminated pushbutton 16 mm Aluminium, maintain, Front dimension Ø 18 mm</b>									
Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.2112</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.2113</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.2114</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.2115</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.2116</b>	3	2	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.2122</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.2123</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.2124</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.2125</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.2126</b>	3	2	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.2132</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.2133</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.2134</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.2135</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.2136</b>	3	2	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.2142</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.2143</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.2144</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.2145</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.2146</b>	3	2	0.018 kg

illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.2152</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.2153</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.2154</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.2155</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.2156</b>	3	2	0.018 kg



**Illuminated pushbutton 16 mm Aluminium, maintain, Front dimension Ø 18 mm**

Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.2212</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.2213</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.2214</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.2215</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.2216</b>	3	2	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.2222</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.2223</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.2224</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.2225</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.2226</b>	3	2	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.2232</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.2233</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.2234</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.2235</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.2236</b>	3	2	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.2242</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.2243</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.2244</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.2245</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.2246</b>	3	2	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.2252</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.2253</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.2254</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.2255</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-4551.2256</b>	3	2	0.021 kg



**Illuminated pushbutton 16 mm stainless-steel, momentary, Front dimension Ø 18 mm**

Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4152.1112</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4152.1113</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4152.1114</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4152.1115</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4152.1116</b>	3	1	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4152.1122</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4152.1123</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4152.1124</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4152.1125</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4152.1126</b>	3	1	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4152.1132</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4152.1133</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4152.1134</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4152.1135</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4152.1136</b>	3	1	0.018 kg

# 82 Flush design

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4152.1142</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4152.1143</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4152.1144</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4152.1145</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4152.1146</b>	3	1	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4152.1152</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4152.1153</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4152.1154</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4152.1155</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4152.1156</b>	3	1	0.018 kg



### Illuminated pushbutton 16 mm stainless-steel, momentary, Front dimension Ø 18 mm

Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4152.1212</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4152.1213</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4152.1214</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4152.1215</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4152.1216</b>	3	1	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4152.1222</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4152.1223</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4152.1224</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4152.1225</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4152.1226</b>	3	1	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4152.1232</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4152.1233</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4152.1234</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4152.1235</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4152.1236</b>	3	1	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4152.1242</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4152.1243</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4152.1244</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4152.1245</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4152.1246</b>	3	1	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4152.1252</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4152.1253</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4152.1254</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4152.1255</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4152.1256</b>	3	1	0.021 kg



### Illuminated pushbutton 16 mm stainless-steel, maintain, Front dimension Ø 18 mm

Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4152.2112</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4152.2113</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4152.2114</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4152.2115</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4152.2116</b>	3	2	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4152.2122</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4152.2123</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4152.2124</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4152.2125</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4152.2126</b>	3	2	0.018 kg

illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4152.2132</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4152.2133</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4152.2134</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4152.2135</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4152.2136</b>	3	2	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4152.2142</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4152.2143</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4152.2144</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4152.2145</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4152.2146</b>	3	2	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4152.2152</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4152.2153</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4152.2154</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4152.2155</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4152.2156</b>	3	2	0.018 kg



**Illuminated pushbutton 16 mm stainless-steel, maintain, Front dimension Ø 18 mm**

Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4152.2212</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4152.2213</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4152.2214</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4152.2215</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4152.2216</b>	3	2	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4152.2222</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4152.2223</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4152.2224</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4152.2225</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4152.2226</b>	3	2	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4152.2232</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4152.2233</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4152.2234</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4152.2235</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4152.2236</b>	3	2	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4152.2242</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4152.2243</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4152.2244</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4152.2245</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4152.2246</b>	3	2	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4152.2252</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4152.2253</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4152.2254</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4152.2255</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4152.2256</b>	3	2	0.021 kg

# 82 Flush design

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
 <p><b>Illuminated pushbutton 16 mm stainless-steel chrome-coloured, momentary, Front dimension Ø 18 mm</b></p>									
Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4252.1112</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4252.1113</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4252.1114</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4252.1115</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4252.1116</b>	3	1	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4252.1122</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4252.1123</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4252.1124</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4252.1125</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4252.1126</b>	3	1	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4252.1132</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4252.1133</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4252.1134</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4252.1135</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4252.1136</b>	3	1	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4252.1142</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4252.1143</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4252.1144</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4252.1145</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4252.1146</b>	3	1	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4252.1152</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4252.1153</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4252.1154</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4252.1155</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4252.1156</b>	3	1	0.018 kg
 <p><b>Illuminated pushbutton 16 mm stainless-steel chrome-coloured, momentary, Front dimension Ø 18 mm</b></p>									
Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4252.1212</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4252.1213</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4252.1214</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4252.1215</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4252.1216</b>	3	1	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4252.1222</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4252.1223</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4252.1224</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4252.1225</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4252.1226</b>	3	1	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4252.1232</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4252.1233</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4252.1234</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4252.1235</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4252.1236</b>	3	1	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4252.1242</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4252.1243</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4252.1244</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4252.1245</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4252.1246</b>	3	1	0.021 kg

illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4252.1252</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4252.1253</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4252.1254</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4252.1255</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4252.1256</b>	3	1	0.021 kg



**Illuminated pushbutton 16 mm stainless-steel chrome-coloured, maintain, Front dimension Ø 18 mm**

Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4252.2112</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4252.2113</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4252.2114</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4252.2115</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4252.2116</b>	3	2	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4252.2122</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4252.2123</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4252.2124</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4252.2125</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4252.2126</b>	3	2	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4252.2132</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4252.2133</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4252.2134</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4252.2135</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4252.2136</b>	3	2	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4252.2142</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4252.2143</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4252.2144</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4252.2145</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4252.2146</b>	3	2	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4252.2152</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4252.2153</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4252.2154</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4252.2155</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4252.2156</b>	3	2	0.018 kg



**Illuminated pushbutton 16 mm stainless-steel chrome-coloured, maintain, Front dimension Ø 18 mm**

Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4252.2212</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4252.2213</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4252.2214</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4252.2215</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4252.2216</b>	3	2	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4252.2222</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4252.2223</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4252.2224</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4252.2225</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4252.2226</b>	3	2	0.021 kg

# 82 Flush design

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4252.2232</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4252.2233</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4252.2234</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4252.2235</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4252.2236</b>	3	2	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4252.2242</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4252.2243</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4252.2244</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4252.2245</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4252.2246</b>	3	2	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4252.2252</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4252.2253</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4252.2254</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4252.2255</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4252.2256</b>	3	2	0.021 kg



### Illuminated pushbutton 16 mm Brass, momentary, Front dimension Ø 18 mm

Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4352.1112</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4352.1113</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4352.1114</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4352.1115</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4352.1116</b>	3	1	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4352.1122</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4352.1123</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4352.1124</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4352.1125</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4352.1126</b>	3	1	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4352.1132</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4352.1133</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4352.1134</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4352.1135</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4352.1136</b>	3	1	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4352.1142</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4352.1143</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4352.1144</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4352.1145</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4352.1146</b>	3	1	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4352.1152</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4352.1153</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4352.1154</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4352.1155</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4352.1156</b>	3	1	0.018 kg



### Illuminated pushbutton 16 mm Brass, momentary, Front dimension Ø 18 mm

Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4352.1212</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4352.1213</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4352.1214</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4352.1215</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4352.1216</b>	3	1	0.021 kg

illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4352.1222</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4352.1223</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4352.1224</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4352.1225</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4352.1226</b>	3	1	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4352.1232</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4352.1233</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4352.1234</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4352.1235</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4352.1236</b>	3	1	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4352.1242</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4352.1243</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4352.1244</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4352.1245</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4352.1246</b>	3	1	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4352.1252</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4352.1253</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4352.1254</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4352.1255</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4352.1256</b>	3	1	0.021 kg



#### Illuminated pushbutton 16 mm Brass, maintain, Front dimension Ø 18 mm

Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4352.2112</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4352.2113</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4352.2114</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4352.2115</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4352.2116</b>	3	2	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4352.2122</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4352.2123</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4352.2124</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4352.2125</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4352.2126</b>	3	2	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4352.2132</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4352.2133</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4352.2134</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4352.2135</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4352.2136</b>	3	2	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4352.2142</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4352.2143</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4352.2144</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4352.2145</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4352.2146</b>	3	2	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4352.2152</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4352.2153</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4352.2154</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4352.2155</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4352.2156</b>	3	2	0.018 kg

# 82 Flush design

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
 <p><b>Illuminated pushbutton 16 mm Brass, maintain, Front dimension Ø 18 mm</b></p>									
Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4352.2212</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4352.2213</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4352.2214</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4352.2215</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4352.2216</b>	3	2	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4352.2222</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4352.2223</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4352.2224</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4352.2225</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4352.2226</b>	3	2	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4352.2232</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4352.2233</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4352.2234</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4352.2235</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4352.2236</b>	3	2	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4352.2242</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4352.2243</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4352.2244</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4352.2245</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4352.2246</b>	3	2	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4352.2252</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4352.2253</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4352.2254</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4352.2255</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4352.2256</b>	3	2	0.021 kg
 <p><b>Illuminated pushbutton 16 mm Aluminium, momentary, Front dimension Ø 18 mm</b></p>									
Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4552.1112</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4552.1113</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4552.1114</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4552.1115</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4552.1116</b>	3	1	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4552.1122</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4552.1123</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4552.1124</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4552.1125</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4552.1126</b>	3	1	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4552.1132</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4552.1133</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4552.1134</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4552.1135</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4552.1136</b>	3	1	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4552.1142</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4552.1143</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4552.1144</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4552.1145</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4552.1146</b>	3	1	0.018 kg

illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4552.1152</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4552.1153</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4552.1154</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4552.1155</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4552.1156</b>	3	1	0.018 kg



#### Illuminated pushbutton 16 mm Aluminium, momentary, Front dimension Ø 18 mm

Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4552.1212</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4552.1213</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4552.1214</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4552.1215</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4552.1216</b>	3	1	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4552.1222</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4552.1223</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4552.1224</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4552.1225</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4552.1226</b>	3	1	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4552.1232</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4552.1233</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4552.1234</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4552.1235</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4552.1236</b>	3	1	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4552.1242</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4552.1243</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4552.1244</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4552.1245</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4552.1246</b>	3	1	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4552.1252</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4552.1253</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4552.1254</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4552.1255</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4552.1256</b>	3	1	0.021 kg



#### Illuminated pushbutton 16 mm Aluminium, maintain, Front dimension Ø 18 mm

Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4552.2112</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4552.2113</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4552.2114</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4552.2115</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4552.2116</b>	3	2	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4552.2122</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4552.2123</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4552.2124</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4552.2125</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4552.2126</b>	3	2	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4552.2132</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4552.2133</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4552.2134</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4552.2135</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4552.2136</b>	3	2	0.018 kg

# 82 Flush design


Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4552.2142</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4552.2143</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4552.2144</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4552.2145</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4552.2146</b>	3	2	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4552.2152</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4552.2153</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4552.2154</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4552.2155</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4552.2156</b>	3	2	0.018 kg



### Illuminated pushbutton 16 mm Aluminium, maintain, Front dimension Ø 18 mm

Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4552.2212</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4552.2213</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4552.2214</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4552.2215</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4552.2216</b>	3	2	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4552.2222</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4552.2223</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4552.2224</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4552.2225</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4552.2226</b>	3	2	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4552.2232</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4552.2233</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4552.2234</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4552.2235</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4552.2236</b>	3	2	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4552.2242</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4552.2243</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4552.2244</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4552.2245</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4552.2246</b>	3	2	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-4552.2252</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-4552.2253</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-4552.2254</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-4552.2255</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-4552.2256</b>	3	2	0.021 kg


The component layouts you will find from page 103



Illuminated pushbutton 19 mm, IP 65 & IP 67




Product can differ from the current configuration.



Dimensions [mm]  
L1 = Solder/Plug-in terminal 2.8 x 0.5 mm,  
X = Screw terminal


Equipment consisting of (schematic overview)



Each Part Number listed below includes all the black components shown in the 3D-drawing.

Additional Information

- Contacts: 1 chance over (NC/NO)



Mounting cut-outs [mm]

Illustration	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
<p><b>Illuminated pushbutton 19 mm stainless-steel, momentary, Front dimension Ø 22 mm</b></p>	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.1112</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.1113</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.1114</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.1115</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.1116</b>	3	1	0.018 kg
	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.1122</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.1123</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.1124</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.1125</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.1126</b>	3	1	0.018 kg
	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.1132</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.1133</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.1134</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.1135</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.1136</b>	3	1	0.018 kg
	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.1142</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.1143</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.1144</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.1145</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.1146</b>	3	1	0.018 kg

# 82 Flush design

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.1152</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.1153</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.1154</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.1155</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.1156</b>	3	1	0.018 kg



### Illuminated pushbutton 19 mm stainless-steel, momentary, Front dimension Ø 22 mm

Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.1212</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.1213</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.1214</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.1215</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.1216</b>	3	1	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.1222</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.1223</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.1224</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.1225</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.1226</b>	3	1	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.1232</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.1233</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.1234</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.1235</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.1236</b>	3	1	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.1242</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.1243</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.1244</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.1245</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.1246</b>	3	1	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.1252</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.1253</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.1254</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.1255</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.1256</b>	3	1	0.021 kg



### Illuminated pushbutton 19 mm stainless-steel, maintain, Front dimension Ø 22 mm

Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.2112</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.2113</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.2114</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.2115</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.2116</b>	3	2	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.2122</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.2123</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.2124</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.2125</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.2126</b>	3	2	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.2132</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.2133</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.2134</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.2135</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.2136</b>	3	2	0.018 kg

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.2142</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.2143</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.2144</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.2145</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.2146</b>	3	2	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.2152</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.2153</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.2154</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.2155</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.2156</b>	3	2	0.018 kg


**Illuminated pushbutton 19 mm stainless-steel, maintain, Front dimension Ø 22 mm**

Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.2212</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.2213</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.2214</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.2215</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.2216</b>	3	2	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.2222</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.2223</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.2224</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.2225</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.2226</b>	3	2	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.2232</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.2233</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.2234</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.2235</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.2236</b>	3	2	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.2242</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.2243</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.2244</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.2245</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.2246</b>	3	2	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.2252</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.2253</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.2254</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.2255</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5151.2256</b>	3	2	0.021 kg


**Illuminated pushbutton 19 mm stainless-steel chrome-coloured, momentary, Front dimension Ø 22 mm**

Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.1112</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.1113</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.1114</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.1115</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.1116</b>	3	1	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.1122</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.1123</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.1124</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.1125</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.1126</b>	3	1	0.018 kg

# 82 Flush design

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.1132</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.1133</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.1134</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.1135</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.1136</b>	3	1	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.1142</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.1143</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.1144</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.1145</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.1146</b>	3	1	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.1152</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.1153</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.1154</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.1155</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.1156</b>	3	1	0.018 kg



### Illuminated pushbutton 19 mm stainless-steel chrome-coloured, momentary, Front dimension Ø 22 mm

Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.1212</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.1213</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.1214</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.1215</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.1216</b>	3	1	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.1222</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.1223</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.1224</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.1225</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.1226</b>	3	1	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.1232</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.1233</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.1234</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.1235</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.1236</b>	3	1	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.1242</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.1243</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.1244</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.1245</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.1246</b>	3	1	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.1252</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.1253</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.1254</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.1255</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.1256</b>	3	1	0.021 kg

illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
 <p><b>Illuminated pushbutton 19 mm stainless-steel chrome-coloured, maintain, Front dimension Ø 22 mm</b></p>									
Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.2112</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.2113</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.2114</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.2115</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.2116</b>	3	2	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.2122</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.2123</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.2124</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.2125</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.2126</b>	3	2	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.2132</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.2133</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.2134</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.2135</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.2136</b>	3	2	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.2142</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.2143</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.2144</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.2145</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.2146</b>	3	2	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.2152</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.2153</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.2154</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.2155</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.2156</b>	3	2	0.018 kg

 <p><b>Illuminated pushbutton 19 mm stainless-steel chrome-coloured, maintain, Front dimension Ø 22 mm</b></p>									
Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.2212</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.2213</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.2214</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.2215</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.2216</b>	3	2	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.2222</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.2223</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.2224</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.2225</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.2226</b>	3	2	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.2232</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.2233</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.2234</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.2235</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.2236</b>	3	2	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.2242</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.2243</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.2244</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.2245</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.2246</b>	3	2	0.021 kg

# 82 Flush design

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.2252</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.2253</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.2254</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.2255</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5251.2256</b>	3	2	0.021 kg



### Illuminated pushbutton 19 mm Brass, momentary, Front dimension Ø 22 mm

Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.1112</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.1113</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.1114</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.1115</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.1116</b>	3	1	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.1122</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.1123</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.1124</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.1125</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.1126</b>	3	1	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.1132</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.1133</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.1134</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.1135</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.1136</b>	3	1	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.1142</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.1143</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.1144</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.1145</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.1146</b>	3	1	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.1152</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.1153</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.1154</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.1155</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.1156</b>	3	1	0.018 kg



### Illuminated pushbutton 19 mm Brass, momentary, Front dimension Ø 22 mm

Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.1212</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.1213</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.1214</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.1215</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.1216</b>	3	1	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.1222</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.1223</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.1224</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.1225</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.1226</b>	3	1	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.1232</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.1233</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.1234</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.1235</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.1236</b>	3	1	0.021 kg

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.1242</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.1243</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.1244</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.1245</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.1246</b>	3	1	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.1252</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.1253</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.1254</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.1255</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.1256</b>	3	1	0.021 kg



#### Illuminated pushbutton 19 mm Brass, maintain, Front dimension Ø 22 mm

Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.2112</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.2113</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.2114</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.2115</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.2116</b>	3	2	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.2122</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.2123</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.2124</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.2125</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.2126</b>	3	2	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.2132</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.2133</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.2134</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.2135</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.2136</b>	3	2	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.2142</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.2143</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.2144</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.2145</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.2146</b>	3	2	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.2152</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.2153</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.2154</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.2155</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.2156</b>	3	2	0.018 kg



#### Illuminated pushbutton 19 mm Brass, maintain, Front dimension Ø 22 mm

Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.2212</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.2213</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.2214</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.2215</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.2216</b>	3	2	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.2222</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.2223</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.2224</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.2225</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.2226</b>	3	2	0.021 kg

# 82 Flush design

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.2232</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.2233</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.2234</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.2235</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.2236</b>	3	2	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.2242</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.2243</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.2244</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.2245</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.2246</b>	3	2	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.2252</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.2253</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.2254</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.2255</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5351.2256</b>	3	2	0.021 kg



## Illuminated pushbutton 19 mm Aluminium, momentary, Front dimension Ø 22 mm

Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.1112</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.1113</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.1114</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.1115</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.1116</b>	3	1	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.1122</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.1123</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.1124</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.1125</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.1126</b>	3	1	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.1132</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.1133</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.1134</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.1135</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.1136</b>	3	1	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.1142</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.1143</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.1144</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.1145</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.1146</b>	3	1	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.1152</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.1153</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.1154</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.1155</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.1156</b>	3	1	0.018 kg

illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
 <p><b>Illuminated pushbutton 19 mm Aluminium, momentary, Front dimension Ø 22 mm</b></p>									
Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.1212</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.1213</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.1214</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.1215</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.1216</b>	3	1	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.1222</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.1223</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.1224</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.1225</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.1226</b>	3	1	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.1232</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.1233</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.1234</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.1235</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.1236</b>	3	1	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.1242</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.1243</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.1244</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.1245</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.1246</b>	3	1	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.1252</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.1253</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.1254</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.1255</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.1256</b>	3	1	0.021 kg

 <p><b>Illuminated pushbutton 19 mm Aluminium, maintain, Front dimension Ø 22 mm</b></p>									
Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.2112</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.2113</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.2114</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.2115</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.2116</b>	3	2	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.2122</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.2123</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.2124</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.2125</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.2126</b>	3	2	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.2132</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.2133</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.2134</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.2135</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.2136</b>	3	2	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.2142</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.2143</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.2144</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.2145</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.2146</b>	3	2	0.018 kg

# 82 Flush design

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.2152</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.2153</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.2154</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.2155</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.2156</b>	3	2	0.018 kg



### Illuminated pushbutton 19 mm Aluminium, maintain, Front dimension Ø 22 mm

Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.2212</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.2213</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.2214</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.2215</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.2216</b>	3	2	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.2222</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.2223</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.2224</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.2225</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.2226</b>	3	2	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.2232</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.2233</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.2234</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.2235</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.2236</b>	3	2	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.2242</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.2243</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.2244</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.2245</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.2246</b>	3	2	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.2252</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.2253</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.2254</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.2255</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-5551.2256</b>	3	2	0.021 kg



### Illuminated pushbutton 19 mm stainless-steel, momentary, Front dimension Ø 22 mm

Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5152.1112</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5152.1113</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5152.1114</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5152.1115</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5152.1116</b>	3	1	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5152.1122</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5152.1123</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5152.1124</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5152.1125</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5152.1126</b>	3	1	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5152.1132</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5152.1133</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5152.1134</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5152.1135</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5152.1136</b>	3	1	0.018 kg

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5152.1142</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5152.1143</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5152.1144</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5152.1145</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5152.1146</b>	3	1	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5152.1152</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5152.1153</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5152.1154</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5152.1155</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5152.1156</b>	3	1	0.018 kg



### illuminated pushbutton 19 mm stainless-steel, momentary, Front dimension Ø 22 mm

Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5152.1212</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5152.1213</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5152.1214</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5152.1215</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5152.1216</b>	3	1	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5152.1222</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5152.1223</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5152.1224</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5152.1225</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5152.1226</b>	3	1	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5152.1232</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5152.1233</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5152.1234</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5152.1235</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5152.1236</b>	3	1	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5152.1242</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5152.1243</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5152.1244</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5152.1245</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5152.1246</b>	3	1	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5152.1252</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5152.1253</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5152.1254</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5152.1255</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5152.1256</b>	3	1	0.021 kg



### illuminated pushbutton 19 mm stainless-steel, maintain, Front dimension Ø 22 mm

Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5152.2112</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5152.2113</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5152.2114</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5152.2115</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5152.2116</b>	3	2	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5152.2122</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5152.2123</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5152.2124</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5152.2125</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5152.2126</b>	3	2	0.018 kg

# 82 Flush design

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5152.2132</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5152.2133</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5152.2134</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5152.2135</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5152.2136</b>	3	2	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5152.2142</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5152.2143</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5152.2144</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5152.2145</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5152.2146</b>	3	2	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5152.2152</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5152.2153</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5152.2154</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5152.2155</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5152.2156</b>	3	2	0.018 kg
 <p><b>Illuminated pushbutton 19 mm stainless-steel, maintain, Front dimension Ø 22 mm</b></p>									
Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5152.2212</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5152.2213</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5152.2214</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5152.2215</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5152.2216</b>	3	2	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5152.2222</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5152.2223</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5152.2224</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5152.2225</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5152.2226</b>	3	2	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5152.2232</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5152.2233</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5152.2234</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5152.2235</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5152.2236</b>	3	2	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5152.2242</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5152.2243</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5152.2244</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5152.2245</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5152.2246</b>	3	2	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5152.2252</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5152.2253</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5152.2254</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5152.2255</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5152.2256</b>	3	2	0.021 kg

illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
 <p><b>Illuminated pushbutton 19 mm stainless-steel chrome-coloured, momentary, Front dimension Ø 22 mm</b></p>									
Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5252.1112</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5252.1113</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5252.1114</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5252.1115</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5252.1116</b>	3	1	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5252.1122</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5252.1123</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5252.1124</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5252.1125</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5252.1126</b>	3	1	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5252.1132</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5252.1133</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5252.1134</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5252.1135</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5252.1136</b>	3	1	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5252.1142</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5252.1143</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5252.1144</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5252.1145</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5252.1146</b>	3	1	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5252.1152</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5252.1153</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5252.1154</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5252.1155</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5252.1156</b>	3	1	0.018 kg

 <p><b>Illuminated pushbutton 19 mm stainless-steel chrome-coloured, momentary, Front dimension Ø 22 mm</b></p>									
Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5252.1212</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5252.1213</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5252.1214</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5252.1215</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5252.1216</b>	3	1	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5252.1222</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5252.1223</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5252.1224</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5252.1225</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5252.1226</b>	3	1	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5252.1232</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5252.1233</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5252.1234</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5252.1235</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5252.1236</b>	3	1	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5252.1242</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5252.1243</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5252.1244</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5252.1245</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5252.1246</b>	3	1	0.021 kg

# 82 Flush design

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5252.1252</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5252.1253</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5252.1254</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5252.1255</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5252.1256</b>	3	1	0.021 kg



### Illuminated pushbutton 19 mm stainless-steel chrome-coloured, maintain, Front dimension Ø 22 mm

Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5252.2112</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5252.2113</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5252.2114</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5252.2115</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5252.2116</b>	3	2	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5252.2122</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5252.2123</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5252.2124</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5252.2125</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5252.2126</b>	3	2	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5252.2132</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5252.2133</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5252.2134</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5252.2135</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5252.2136</b>	3	2	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5252.2142</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5252.2143</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5252.2144</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5252.2145</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5252.2146</b>	3	2	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5252.2152</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5252.2153</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5252.2154</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5252.2155</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5252.2156</b>	3	2	0.018 kg



### Illuminated pushbutton 19 mm stainless-steel chrome-coloured, maintain, Front dimension Ø 22 mm

Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5252.2212</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5252.2213</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5252.2214</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5252.2215</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5252.2216</b>	3	2	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5252.2222</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5252.2223</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5252.2224</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5252.2225</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5252.2226</b>	3	2	0.021 kg

illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5252.2232</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5252.2233</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5252.2234</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5252.2235</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5252.2236</b>	3	2	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5252.2242</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5252.2243</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5252.2244</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5252.2245</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5252.2246</b>	3	2	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5252.2252</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5252.2253</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5252.2254</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5252.2255</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5252.2256</b>	3	2	0.021 kg



**Illuminated pushbutton 19 mm Brass, momentary, Front dimension Ø 22 mm**

Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5352.1112</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5352.1113</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5352.1114</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5352.1115</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5352.1116</b>	3	1	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5352.1122</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5352.1123</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5352.1124</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5352.1125</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5352.1126</b>	3	1	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5352.1132</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5352.1133</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5352.1134</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5352.1135</b>	3	1	0.018 kg
Ring with green LED	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5352.1136</b>	3	1	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5352.1142</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5352.1143</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5352.1144</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5352.1145</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5352.1146</b>	3	1	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5352.1152</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5352.1153</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5352.1154</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5352.1155</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5352.1156</b>	3	1	0.018 kg

# 82 Flush design

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
 <p><b>Illuminated pushbutton 19 mm Brass, momentary, Front dimension Ø 22 mm</b></p>									
Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5352.1212</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5352.1213</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5352.1214</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5352.1215</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5352.1216</b>	3	1	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5352.1222</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5352.1223</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5352.1224</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5352.1225</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5352.1226</b>	3	1	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5352.1232</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5352.1233</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5352.1234</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5352.1235</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5352.1236</b>	3	1	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5352.1242</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5352.1243</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5352.1244</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5352.1245</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5352.1246</b>	3	1	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5352.1252</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5352.1253</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5352.1254</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5352.1255</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5352.1256</b>	3	1	0.021 kg
 <p><b>Illuminated pushbutton 19 mm Brass, maintain, Front dimension Ø 22 mm</b></p>									
Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5352.2112</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5352.2113</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5352.2114</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5352.2115</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5352.2116</b>	3	2	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5352.2122</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5352.2123</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5352.2124</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5352.2125</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5352.2126</b>	3	2	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5352.2132</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5352.2133</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5352.2134</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5352.2135</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5352.2136</b>	3	2	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5352.2142</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5352.2143</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5352.2144</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5352.2145</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5352.2146</b>	3	2	0.018 kg

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5352.2152</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5352.2153</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5352.2154</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5352.2155</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5352.2156</b>	3	2	0.018 kg



#### Illuminated pushbutton 19 mm Brass, maintain, Front dimension Ø 22 mm

Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5352.2212</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5352.2213</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5352.2214</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5352.2215</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5352.2216</b>	3	2	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5352.2222</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5352.2223</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5352.2224</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5352.2225</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5352.2226</b>	3	2	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5352.2232</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5352.2233</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5352.2234</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5352.2235</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5352.2236</b>	3	2	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5352.2242</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5352.2243</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5352.2244</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5352.2245</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5352.2246</b>	3	2	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5352.2252</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5352.2253</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5352.2254</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5352.2255</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5352.2256</b>	3	2	0.021 kg



#### Illuminated pushbutton 19 mm Aluminium, momentary, Front dimension Ø 22 mm

Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5552.1112</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5552.1113</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5552.1114</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5552.1115</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5552.1116</b>	3	1	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5552.1122</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5552.1123</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5552.1124</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5552.1125</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5552.1126</b>	3	1	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5552.1132</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5552.1133</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5552.1134</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5552.1135</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5552.1136</b>	3	1	0.018 kg

# 82 Flush design

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5552.1142</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5552.1143</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5552.1144</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5552.1145</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5552.1146</b>	3	1	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5552.1152</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5552.1153</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5552.1154</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5552.1155</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5552.1156</b>	3	1	0.018 kg



### Illuminated pushbutton 19 mm Aluminium, momentary, Front dimension Ø 22 mm

Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5552.1212</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5552.1213</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5552.1214</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5552.1215</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5552.1216</b>	3	1	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5552.1222</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5552.1223</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5552.1224</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5552.1225</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5552.1226</b>	3	1	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5552.1232</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5552.1233</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5552.1234</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5552.1235</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5552.1236</b>	3	1	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5552.1242</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5552.1243</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5552.1244</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5552.1245</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5552.1246</b>	3	1	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5552.1252</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5552.1253</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5552.1254</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5552.1255</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5552.1256</b>	3	1	0.021 kg



### Illuminated pushbutton 19 mm Aluminium, maintain, Front dimension Ø 22 mm

Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5552.2112</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5552.2113</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5552.2114</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5552.2115</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5552.2116</b>	3	2	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5552.2122</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5552.2123</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5552.2124</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5552.2125</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5552.2126</b>	3	2	0.018 kg


illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5552.2132</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5552.2133</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5552.2134</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5552.2135</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5552.2136</b>	3	2	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5552.2142</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5552.2143</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5552.2144</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5552.2145</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5552.2146</b>	3	2	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5552.2152</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5552.2153</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5552.2154</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5552.2155</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5552.2156</b>	3	2	0.018 kg



**Illuminated pushbutton 19 mm Aluminium, maintain, Front dimension Ø 22 mm**

Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5552.2212</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5552.2213</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5552.2214</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5552.2215</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5552.2216</b>	3	2	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5552.2222</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5552.2223</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5552.2224</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5552.2225</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5552.2226</b>	3	2	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5552.2232</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5552.2233</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5552.2234</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5552.2235</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5552.2236</b>	3	2	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5552.2242</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5552.2243</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5552.2244</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5552.2245</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5552.2246</b>	3	2	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-5552.2252</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-5552.2253</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-5552.2254</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-5552.2255</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-5552.2256</b>	3	2	0.021 kg

The component layouts you will find from page 103




# 82 Flush design

## Illuminated pushbutton 22 mm, IP 65 & IP 67




Product can differ from the current configuration.




Dimensions [mm]  
L1 = Solder/Plug-in terminal 2.8 x 0.5 mm,  
X = Screw terminal

### Equipment consisting of (schematic overview)



### Additional Information

- Contacts: 1 chance over (NC/NO)



Mounting cut-outs [mm]

Each Part Number listed below includes all the black components shown in the 3D-drawing.

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
 <p><b>Illuminated pushbutton 22 mm stainless-steel, momentary, Front dimension Ø 25 mm</b></p>									
Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.1112</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.1113</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.1114</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.1115</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.1116</b>	3	1	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.1122</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.1123</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.1124</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.1125</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.1126</b>	3	1	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.1132</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.1133</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.1134</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.1135</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.1136</b>	3	1	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.1142</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.1143</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.1144</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.1145</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.1146</b>	3	1	0.018 kg

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.1152</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.1153</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.1154</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.1155</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.1156</b>	3	1	0.018 kg


**Illuminated pushbutton 22 mm stainless-steel, momentary, Front dimension Ø 25 mm**

Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.1212</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.1213</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.1214</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.1215</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.1216</b>	3	1	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.1222</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.1223</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.1224</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.1225</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.1226</b>	3	1	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.1232</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.1233</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.1234</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.1235</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.1236</b>	3	1	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.1242</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.1243</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.1244</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.1245</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.1246</b>	3	1	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.1252</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.1253</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.1254</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.1255</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.1256</b>	3	1	0.021 kg


**Illuminated pushbutton 22 mm stainless-steel, maintain, Front dimension Ø 25 mm**

Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.2112</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.2113</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.2114</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.2115</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.2116</b>	3	2	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.2122</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.2123</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.2124</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.2125</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.2126</b>	3	2	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.2132</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.2133</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.2134</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.2135</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.2136</b>	3	2	0.018 kg

# 82 Flush design

illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.2142</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.2143</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.2144</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.2145</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.2146</b>	3	2	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.2152</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.2153</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.2154</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.2155</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.2156</b>	3	2	0.018 kg



### illuminated pushbutton 22 mm stainless-steel, maintain, Front dimension Ø 25 mm

Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.2212</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.2213</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.2214</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.2215</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.2216</b>	3	2	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.2222</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.2223</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.2224</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.2225</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.2226</b>	3	2	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.2232</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.2233</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.2234</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.2235</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.2236</b>	3	2	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.2242</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.2243</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.2244</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.2245</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.2246</b>	3	2	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.2252</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.2253</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.2254</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.2255</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6151.2256</b>	3	2	0.021 kg



### illuminated pushbutton 22 mm stainless-steel chrome-coloured, momentary, Front dimension Ø 25 mm

Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.1112</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.1113</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.1114</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.1115</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.1116</b>	3	1	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.1122</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.1123</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.1124</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.1125</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.1126</b>	3	1	0.018 kg

illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.1132</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.1133</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.1134</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.1135</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.1136</b>	3	1	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.1142</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.1143</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.1144</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.1145</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.1146</b>	3	1	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.1152</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.1153</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.1154</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.1155</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.1156</b>	3	1	0.018 kg



**Illuminated pushbutton 22 mm stainless-steel chrome-coloured, momentary, Front dimension Ø 25 mm**

Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.1212</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.1213</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.1214</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.1215</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.1216</b>	3	1	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.1222</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.1223</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.1224</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.1225</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.1226</b>	3	1	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.1232</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.1233</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.1234</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.1235</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.1236</b>	3	1	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.1242</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.1243</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.1244</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.1245</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.1246</b>	3	1	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.1252</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.1253</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.1254</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.1255</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.1256</b>	3	1	0.021 kg

# 82 Flush design

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
 <p><b>Illuminated pushbutton 22 mm stainless-steel chrome-coloured, maintain, Front dimension Ø 25 mm</b></p>									
Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.2112</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.2113</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.2114</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.2115</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.2116</b>	3	2	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.2122</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.2123</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.2124</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.2125</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.2126</b>	3	2	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.2132</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.2133</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.2134</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.2135</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.2136</b>	3	2	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.2142</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.2143</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.2144</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.2145</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.2146</b>	3	2	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.2152</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.2153</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.2154</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.2155</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.2156</b>	3	2	0.018 kg
 <p><b>Illuminated pushbutton 22 mm stainless-steel chrome-coloured, maintain, Front dimension Ø 25 mm</b></p>									
Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.2212</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.2213</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.2214</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.2215</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.2216</b>	3	2	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.2222</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.2223</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.2224</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.2225</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.2226</b>	3	2	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.2232</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.2233</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.2234</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.2235</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.2236</b>	3	2	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.2242</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.2243</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.2244</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.2245</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.2246</b>	3	2	0.021 kg

illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.2252</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.2253</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.2254</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.2255</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6251.2256</b>	3	2	0.021 kg



**Illuminated pushbutton 22 mm Brass, momentary, Front dimension Ø 25 mm**

Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.1112</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.1113</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.1114</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.1115</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.1116</b>	3	1	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.1122</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.1123</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.1124</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.1125</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.1126</b>	3	1	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.1132</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.1133</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.1134</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.1135</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.1136</b>	3	1	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.1142</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.1143</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.1144</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.1145</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.1146</b>	3	1	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.1152</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.1153</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.1154</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.1155</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.1156</b>	3	1	0.018 kg



**Illuminated pushbutton 22 mm Brass, momentary, Front dimension Ø 25 mm**

Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.1212</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.1213</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.1214</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.1215</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.1216</b>	3	1	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.1222</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.1223</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.1224</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.1225</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.1226</b>	3	1	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.1232</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.1233</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.1234</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.1235</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.1236</b>	3	1	0.021 kg

# 82 Flush design

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.1242</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.1243</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.1244</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.1245</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.1246</b>	3	1	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.1252</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.1253</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.1254</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.1255</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.1256</b>	3	1	0.021 kg



### Illuminated pushbutton 22 mm Brass, maintain, Front dimension Ø 25 mm

Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.2112</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.2113</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.2114</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.2115</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.2116</b>	3	2	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.2122</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.2123</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.2124</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.2125</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.2126</b>	3	2	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.2132</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.2133</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.2134</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.2135</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.2136</b>	3	2	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.2142</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.2143</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.2144</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.2145</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.2146</b>	3	2	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.2152</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.2153</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.2154</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.2155</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.2156</b>	3	2	0.018 kg



### Illuminated pushbutton 22 mm Brass, maintain, Front dimension Ø 25 mm

Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.2212</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.2213</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.2214</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.2215</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.2216</b>	3	2	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.2222</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.2223</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.2224</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.2225</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.2226</b>	3	2	0.021 kg

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.2232</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.2233</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.2234</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.2235</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.2236</b>	3	2	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.2242</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.2243</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.2244</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.2245</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.2246</b>	3	2	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.2252</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.2253</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.2254</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.2255</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6351.2256</b>	3	2	0.021 kg



**Illuminated pushbutton 22 mm Aluminium, momentary, Front dimension Ø 25 mm**

Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.1112</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.1113</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.1114</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.1115</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.1116</b>	3	1	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.1122</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.1123</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.1124</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.1125</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.1126</b>	3	1	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.1132</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.1133</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.1134</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.1135</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.1136</b>	3	1	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.1142</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.1143</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.1144</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.1145</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.1146</b>	3	1	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.1152</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.1153</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.1154</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.1155</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.1156</b>	3	1	0.018 kg



**Illuminated pushbutton 22 mm Aluminium, momentary, Front dimension Ø 25 mm**

Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.1212</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.1213</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.1214</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.1215</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.1216</b>	3	1	0.021 kg

# 82 Flush design

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.1222</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.1223</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.1224</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.1225</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.1226</b>	3	1	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.1232</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.1233</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.1234</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.1235</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.1236</b>	3	1	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.1242</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.1243</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.1244</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.1245</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.1246</b>	3	1	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.1252</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.1253</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.1254</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.1255</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.1256</b>	3	1	0.021 kg
 <p><b>Illuminated pushbutton 22 mm Aluminium, maintain, Front dimension Ø 25 mm</b></p>									
Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.2112</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.2113</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.2114</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.2115</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.2116</b>	3	2	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.2122</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.2123</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.2124</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.2125</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.2126</b>	3	2	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.2132</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.2133</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.2134</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.2135</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.2136</b>	3	2	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.2142</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.2143</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.2144</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.2145</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.2146</b>	3	2	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.2152</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.2153</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.2154</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.2155</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.2156</b>	3	2	0.018 kg

Illustration	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
	<b>Illuminated pushbutton 22 mm Aluminium, maintain, Front dimension Ø 25 mm</b>								
Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.2212</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.2213</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.2214</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.2215</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.2216</b>	3	2	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.2222</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.2223</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.2224</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.2225</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.2226</b>	3	2	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.2232</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.2233</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.2234</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.2235</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.2236</b>	3	2	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.2242</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.2243</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.2244</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.2245</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.2246</b>	3	2	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.2252</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.2253</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.2254</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.2255</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Solder 2.8 x 0.5 mm	<b>82-6551.2256</b>	3	2	0.021 kg

	<b>Illuminated pushbutton 22 mm stainless-steel, momentary, Front dimension Ø 25 mm</b>								
Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6152.1112</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6152.1113</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6152.1114</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6152.1115</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6152.1116</b>	3	1	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6152.1122</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6152.1123</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6152.1124</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6152.1125</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6152.1126</b>	3	1	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6152.1132</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6152.1133</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6152.1134</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6152.1135</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6152.1136</b>	3	1	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6152.1142</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6152.1143</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6152.1144</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6152.1145</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6152.1146</b>	3	1	0.018 kg

# 82 Flush design

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6152.1152</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6152.1153</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6152.1154</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6152.1155</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6152.1156</b>	3	1	0.018 kg



## Illuminated pushbutton 22 mm stainless-steel, momentary, Front dimension Ø 25 mm

Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6152.1212</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6152.1213</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6152.1214</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6152.1215</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6152.1216</b>	3	1	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6152.1222</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6152.1223</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6152.1224</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6152.1225</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6152.1226</b>	3	1	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6152.1232</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6152.1233</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6152.1234</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6152.1235</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6152.1236</b>	3	1	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6152.1242</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6152.1243</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6152.1244</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6152.1245</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6152.1246</b>	3	1	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6152.1252</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6152.1253</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6152.1254</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6152.1255</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6152.1256</b>	3	1	0.021 kg



## Illuminated pushbutton 22 mm stainless-steel, maintain, Front dimension Ø 25 mm

Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6152.2112</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6152.2113</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6152.2114</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6152.2115</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6152.2116</b>	3	2	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6152.2122</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6152.2123</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6152.2124</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6152.2125</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6152.2126</b>	3	2	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6152.2132</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6152.2133</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6152.2134</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6152.2135</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6152.2136</b>	3	2	0.018 kg

illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6152.2142</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6152.2143</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6152.2144</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6152.2145</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6152.2146</b>	3	2	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6152.2152</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6152.2153</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6152.2154</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6152.2155</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6152.2156</b>	3	2	0.018 kg



**Illuminated pushbutton 22 mm stainless-steel, maintain, Front dimension Ø 25 mm**

Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6152.2212</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6152.2213</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6152.2214</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6152.2215</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6152.2216</b>	3	2	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6152.2222</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6152.2223</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6152.2224</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6152.2225</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6152.2226</b>	3	2	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6152.2232</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6152.2233</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6152.2234</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6152.2235</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6152.2236</b>	3	2	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6152.2242</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6152.2243</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6152.2244</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6152.2245</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6152.2246</b>	3	2	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6152.2252</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6152.2253</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6152.2254</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6152.2255</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6152.2256</b>	3	2	0.021 kg



**Illuminated pushbutton 22 mm stainless-steel chrome-coloured, momentary, Front dimension Ø 25 mm**

Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6252.1112</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6252.1113</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6252.1114</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6252.1115</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6252.1116</b>	3	1	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6252.1122</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6252.1123</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6252.1124</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6252.1125</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6252.1126</b>	3	1	0.018 kg

# 82 Flush design

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6252.1132</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6252.1133</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6252.1134</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6252.1135</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6252.1136</b>	3	1	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6252.1142</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6252.1143</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6252.1144</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6252.1145</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6252.1146</b>	3	1	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6252.1152</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6252.1153</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6252.1154</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6252.1155</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6252.1156</b>	3	1	0.018 kg



### illuminated pushbutton 22 mm stainless-steel chrome-coloured, momentary, Front dimension Ø 25 mm

Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6252.1212</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6252.1213</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6252.1214</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6252.1215</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6252.1216</b>	3	1	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6252.1222</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6252.1223</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6252.1224</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6252.1225</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6252.1226</b>	3	1	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6252.1232</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6252.1233</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6252.1234</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6252.1235</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6252.1236</b>	3	1	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6252.1242</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6252.1243</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6252.1244</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6252.1245</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6252.1246</b>	3	1	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6252.1252</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6252.1253</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6252.1254</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6252.1255</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6252.1256</b>	3	1	0.021 kg



### illuminated pushbutton 22 mm stainless-steel chrome-coloured, maintain, Front dimension Ø 25 mm

Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6252.2112</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6252.2113</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6252.2114</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6252.2115</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6252.2116</b>	3	2	0.018 kg

illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6252.2122</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6252.2123</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6252.2124</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6252.2125</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6252.2126</b>	3	2	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6252.2132</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6252.2133</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6252.2134</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6252.2135</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6252.2136</b>	3	2	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6252.2142</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6252.2143</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6252.2144</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6252.2145</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6252.2146</b>	3	2	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6252.2152</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6252.2153</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6252.2154</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6252.2155</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6252.2156</b>	3	2	0.018 kg



**Illuminated pushbutton 22 mm stainless-steel chrome-coloured, maintain, Front dimension Ø 25 mm**

Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6252.2212</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6252.2213</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6252.2214</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6252.2215</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6252.2216</b>	3	2	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6252.2222</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6252.2223</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6252.2224</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6252.2225</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6252.2226</b>	3	2	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6252.2232</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6252.2233</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6252.2234</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6252.2235</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6252.2236</b>	3	2	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6252.2242</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6252.2243</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6252.2244</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6252.2245</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6252.2246</b>	3	2	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6252.2252</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6252.2253</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6252.2254</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6252.2255</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6252.2256</b>	3	2	0.021 kg

# 82 Flush design

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
 <p><b>Illuminated pushbutton 22 mm Brass, momentary, Front dimension Ø 25 mm</b></p>									
Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6352.1112</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6352.1113</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6352.1114</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6352.1115</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6352.1116</b>	3	1	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6352.1122</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6352.1123</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6352.1124</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6352.1125</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6352.1126</b>	3	1	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6352.1132</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6352.1133</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6352.1134</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6352.1135</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6352.1136</b>	3	1	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6352.1142</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6352.1143</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6352.1144</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6352.1145</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6352.1146</b>	3	1	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6352.1152</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6352.1153</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6352.1154</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6352.1155</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6352.1156</b>	3	1	0.018 kg
 <p><b>Illuminated pushbutton 22 mm Brass, momentary, Front dimension Ø 25 mm</b></p>									
Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6352.1212</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6352.1213</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6352.1214</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6352.1215</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6352.1216</b>	3	1	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6352.1222</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6352.1223</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6352.1224</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6352.1225</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6352.1226</b>	3	1	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6352.1232</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6352.1233</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6352.1234</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6352.1235</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6352.1236</b>	3	1	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6352.1242</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6352.1243</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6352.1244</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6352.1245</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6352.1246</b>	3	1	0.021 kg

illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6352.1252</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6352.1253</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6352.1254</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6352.1255</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6352.1256</b>	3	1	0.021 kg



**Illuminated pushbutton 22 mm Brass, maintain, Front dimension Ø 25 mm**

Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6352.2112</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6352.2113</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6352.2114</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6352.2115</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6352.2116</b>	3	2	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6352.2122</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6352.2123</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6352.2124</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6352.2125</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6352.2126</b>	3	2	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6352.2132</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6352.2133</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6352.2134</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6352.2135</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6352.2136</b>	3	2	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6352.2142</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6352.2143</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6352.2144</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6352.2145</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6352.2146</b>	3	2	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6352.2152</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6352.2153</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6352.2154</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6352.2155</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6352.2156</b>	3	2	0.018 kg



**Illuminated pushbutton 22 mm Brass, maintain, Front dimension Ø 25 mm**

Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6352.2212</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6352.2213</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6352.2214</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6352.2215</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6352.2216</b>	3	2	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6352.2222</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6352.2223</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6352.2224</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6352.2225</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6352.2226</b>	3	2	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6352.2232</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6352.2233</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6352.2234</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6352.2235</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6352.2236</b>	3	2	0.021 kg

# 82 Flush design

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6352.2242</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6352.2243</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6352.2244</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6352.2245</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6352.2246</b>	3	2	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6352.2252</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6352.2253</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6352.2254</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6352.2255</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6352.2256</b>	3	2	0.021 kg



### Illuminated pushbutton 22 mm Aluminium, momentary, Front dimension Ø 25 mm

Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6552.1112</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6552.1113</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6552.1114</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6552.1115</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6552.1116</b>	3	1	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6552.1122</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6552.1123</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6552.1124</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6552.1125</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6552.1126</b>	3	1	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6552.1132</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6552.1133</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6552.1134</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6552.1135</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6552.1136</b>	3	1	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6552.1142</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6552.1143</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6552.1144</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6552.1145</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6552.1146</b>	3	1	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6552.1152</b>	3	1	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6552.1153</b>	3	1	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6552.1154</b>	3	1	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6552.1155</b>	3	1	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6552.1156</b>	3	1	0.018 kg



### Illuminated pushbutton 22 mm Aluminium, momentary, Front dimension Ø 25 mm

Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6552.1212</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6552.1213</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6552.1214</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6552.1215</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6552.1216</b>	3	1	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6552.1222</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6552.1223</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6552.1224</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6552.1225</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6552.1226</b>	3	1	0.021 kg

illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6552.1232</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6552.1233</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6552.1234</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6552.1235</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6552.1236</b>	3	1	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6552.1242</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6552.1243</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6552.1244</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6552.1245</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6552.1246</b>	3	1	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6552.1252</b>	3	1	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6552.1253</b>	3	1	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6552.1254</b>	3	1	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6552.1255</b>	3	1	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6552.1256</b>	3	1	0.021 kg




**Illuminated pushbutton 22 mm Aluminium, maintain, Front dimension Ø 25 mm**

Ring with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6552.2112</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6552.2113</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6552.2114</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6552.2115</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6552.2116</b>	3	2	0.018 kg
Ring with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6552.2122</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6552.2123</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6552.2124</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6552.2125</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6552.2126</b>	3	2	0.018 kg
Ring with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6552.2132</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6552.2133</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6552.2134</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6552.2135</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6552.2136</b>	3	2	0.018 kg
Ring with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6552.2142</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6552.2143</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6552.2144</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6552.2145</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6552.2146</b>	3	2	0.018 kg
Ring with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6552.2152</b>	3	2	0.018 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6552.2153</b>	3	2	0.018 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6552.2154</b>	3	2	0.018 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6552.2155</b>	3	2	0.018 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6552.2156</b>	3	2	0.018 kg


# 82 Flush design

Illumination	Operating voltage	Operation current	Front ring shape	Lens	Terminal	Part No.	Component layout	Wiring diagram	Weight
 <p><b>Illuminated pushbutton 22 mm Aluminium, maintain, Front dimension Ø 25 mm</b></p>									
Dot with red LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6552.2212</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6552.2213</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6552.2214</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6552.2215</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6552.2216</b>	3	2	0.021 kg
Dot with blue LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6552.2222</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6552.2223</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6552.2224</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6552.2225</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6552.2226</b>	3	2	0.021 kg
Dot with green LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6552.2232</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6552.2233</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6552.2234</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6552.2235</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6552.2236</b>	3	2	0.021 kg
Dot with yellow LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6552.2242</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6552.2243</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6552.2244</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6552.2245</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6552.2246</b>	3	2	0.021 kg
Dot with white LED	6 VAC/DC	15 mA	flush	flat / level with front ring	Screw	<b>82-6552.2252</b>	3	2	0.021 kg
	12 VAC/DC	14 mA	flush	flat / level with front ring	Screw	<b>82-6552.2253</b>	3	2	0.021 kg
	24 VAC/DC	10 mA	flush	flat / level with front ring	Screw	<b>82-6552.2254</b>	3	2	0.021 kg
	110 VAC	2 mA	flush	flat / level with front ring	Screw	<b>82-6552.2255</b>	3	2	0.021 kg
	230 VAC	1.3 mA	flush	flat / level with front ring	Screw	<b>82-6552.2256</b>	3	2	0.021 kg

The component layouts you will find from page 103



Drawings



## Indicator, Pushbutton, Illuminated pushbutton

### Switching system

Snap-action changeover contact normally closed / normally open.  
Switching function momentary or maintain.

### Material

#### Housing

Stainless-steel  
Stainless-steel chrome-coloured  
Brass gold-coloured  
Aluminium natural anodized

#### Terminal housing

Polyamide 66 (PA66)

#### Contact material

Silver alloy

### Mechanical characteristics

#### Mounting cut-out

Ø 16 mm +0.3/+0.1 mm  
Ø 19 mm +0.3/+0.1 mm  
Ø 22 mm +0.3/+0.1 mm

#### Terminals

Soldering/plug-in terminals 2.8 x 0.5 mm  
Screw terminal

#### Tightening torque

5 Nm min. – 12 Nm max. for fixing nut

#### Actuating force

4 ... 7 N

#### Actuating travel

3 mm

#### Mechanical lifetime

Pushbutton momentary 1 Mio. cycles of operation  
Pushbutton maintain 500 000 cycles of operation

#### Resistance to heat of soldering

Hand-soldering max. 380 °C, 3 sek.

### Electrical characteristics

#### Rated Operational Voltage $U_o$

250 VAC

#### Rated Insulation Voltage $U_i$

250 V

### Illumination

LED red, green, blue, yellow and white

LED and series resistor with polarity protection are built in.

LED-Voltage	Tolerance	Current	Consumption
6 VAC/DC	±10%	15 mA	0.1W
12 VAC/DC	±10%	14 mA	0.17W
24 VAC/DC	±10%	10 mA	0.24W
110 VAC	±10%	2 mA	0.22W
230 VAC	±10%	1.3 mA	0.29W

### Contact resistance

<50 mΩ

### Electrical life

50 000 cycles of operation (full load)

### Switch rating IEC 60947-5-1

Switch rating AC cosφ 0.3 service categorie AC-15

Voltage	Current
24 VAC	1 A
110 VAC	1 A
240 VAC	0.5 A

Switch rating DC service categorie DC-13

Voltage	Current
24 VDC	0.7 A
110 VDC	0.2 A
220 VDC	0.1 A

### Switch rating UL 508

Switch rating AC cosφ 0.75 ... 0.8)

Voltage	Current
125 VAC	5 A
250 VAC	3 A

Switch rating DC

Voltage	Current
24 VDC	1 A

### Recommended minimum operational data

Silver contacts

Voltage 17 VAC/DC  
Current 50 mA

### Conventional free air thermal current $I_{th}$

5 A

The maximum current in continuous operation and at ambient temperature must not exceed the quoted maximum values.

### Electrical strength

1500 VAC, 50 Hz 1 min. between life terminals and ground

### Isolation resistance

500 VDC at min. 10 MΩ according to IEC 60512-2

**Environmental conditions**

**Storage temperature**

-40 °C ... +80 °C

**Operating temperature**

-30 °C ... +70 °C

**Front protection**

IP 65 and IP 67, as per IEC 60529

**Impact resistance**

IK 10, as per IEC 62262

**Shock resistance**

max. 500 m/s<sup>2</sup> according to IEC 60068-2-27

**Degree of pollution**

2, as per EN IEC 60947-1

**Vibration resistance**

10 ... 500 Hz, amplitude 1.5 mm p-p according to IEC 60068-2-6

**Climate resistance**

Damp heat, 21 days according to IEC 60512-11

Stainless steel and aluminium versions:

Saline mist, 96 hours according to IEC 60512-11

Brass versions:

Saline mist, 24 hours according to IEC 60512-11

**Approvals**

**Approbations**

CB

UL

C UL

CCC

**Declaration of conformity**

CE

*EAO reserves the right to alter specifications without further notice.*

# 82 Application guidelines

## Suppressor circuits


When switching inductive loads such as relays, DC motors, and DC solenoids, it is always important to absorb surges (e.g. with a diode) to protect the contacts. When these inductive loads are switched off, a counter emf can severely damage switch contacts and greatly shorten lifetime.

Fig. 1 shows an inductive load with a free-wheeling diode connected in parallel. This free-wheeling diode provides a path for the inductor current to flow when the current is interrupted by the switch. Without this free-wheeling diode, the voltage across the coil will be limited only by dielectric breakdown voltages of the circuit or parasitic elements of the coil. This voltage can be kilovolts in amplitude even when nominal circuit voltages are low (e.g. 12VDC) see Fig. 2.


The free-wheeling diode should be chosen so that the reverse breakdown voltage is greater than the voltage driving the inductive load. The DC blocking voltage ( $V_R$ ) of the free-wheeling diode can be found in the datasheet of a diode. The forward current should be equal or greater than the maximum current flowing through the load.

**To get an efficient protection, the free-wheeling diode must be connected as close as possible to the inductive load!**

Switching with inductive load  
Fig. 1



Counter EMF  
over load without free-wheeling diode  
Fig. 2



















Part No.	Page	Part No.	Page
82-6552.1144	100	82-6552.2245	102
82-6552.1145	100	82-6552.2246	102
82-6552.1146	100	82-6552.2252	102
82-6552.1152	100	82-6552.2253	102
82-6552.1153	100	82-6552.2254	102
82-6552.1154	100	82-6552.2255	102
82-6552.1155	100	82-6552.2256	102
82-6552.1156	100	82-6561.1000	43
82-6552.1212	100	82-6561.2000	43
82-6552.1213	100	82-6562.1000	45
82-6552.1214	100	82-6562.2000	45
82-6552.1215	100	82-6571.1000	44
82-6552.1216	100	82-6571.2000	44
82-6552.1222	100	82-6572.1000	45
82-6552.1223	100	82-6572.2000	45
82-6552.1224	100	82-6581.1000	44
82-6552.1225	100	82-6581.2000	44
82-6552.1226	100	82-6582.1000	45
82-6552.1232	101	82-6582.2000	45
82-6552.1233	101		
82-6552.1234	101		
82-6552.1235	101		
82-6552.1236	101		
82-6552.1242	101		
82-6552.1243	101		
82-6552.1244	101		
82-6552.1245	101		
82-6552.1246	101		
82-6552.1252	101		
82-6552.1253	101		
82-6552.1254	101		
82-6552.1255	101		
82-6552.1256	101		
82-6552.2000	45		
82-6552.2112	101		
82-6552.2113	101		
82-6552.2114	101		
82-6552.2115	101		
82-6552.2116	101		
82-6552.2122	101		
82-6552.2123	101		
82-6552.2124	101		
82-6552.2125	101		
82-6552.2126	101		
82-6552.2132	101		
82-6552.2133	101		
82-6552.2134	101		
82-6552.2135	101		
82-6552.2136	101		
82-6552.2142	101		
82-6552.2143	101		
82-6552.2144	101		
82-6552.2145	101		
82-6552.2146	101		
82-6552.2152	101		
82-6552.2153	101		
82-6552.2154	101		
82-6552.2155	101		
82-6552.2156	101		
82-6552.2212	102		
82-6552.2213	102		
82-6552.2214	102		
82-6552.2215	102		
82-6552.2216	102		
82-6552.2222	102		
82-6552.2223	102		
82-6552.2224	102		
82-6552.2225	102		
82-6552.2226	102		
82-6552.2232	102		
82-6552.2233	102		
82-6552.2234	102		
82-6552.2235	102		
82-6552.2236	102		
82-6552.2242	102		
82-6552.2243	102		
82-6552.2244	102		

